


ARCTURUS LED

Product Group: Outdoor accent lighting



Description: A vandal resistant LED bulkhead for outdoor wall applications. Designed to spread light sideways and sealed to IP65
Diffuser: opal polycarbonate, impact resistant
Body: die-cast aluminum, black finish

General data: Mains voltage: 220-240V, 50-60Hz
Power factor: >0,95
Light source: LED
Light source included: Yes
Light distribution type: Direct
LED lifetime, h: 50000/L80B50
Operating temperature range, °C: ta -25...+40
Protection class IEC: I
Ingress protection code: IP65
Mechanical impact resistance: IK08
EEC: A+

Installation: Surface mounted luminaire is designed to be fixed to walls of any type. Push-in terminal, 3x2x2.5mm2

Environment: Outdoor

Application: Facade illumination, transport terminal, parking area, fuel station, public space

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Arcturus LED1x2800 E054 T830 OP	308	264	182	2639	27,1	97	80+	3000	2,40
Arcturus LED1x4000 E055 T830 OP	308	264	182	3845	40,7	95	80+	3000	2,40
Arcturus LED1x2800 E054 T840 OP	308	264	182	2720	27,1	100	80+	4000	2,40
Arcturus LED1x4000 E055 T840 OP	308	264	182	3964	40,7	97	80+	4000	2,40
Arcturus LED1x2800 E054 T850 OP	308	264	182	2759	27,1	102	80+	5000	2,40
Arcturus LED1x4000 E055 T850 OP	308	264	182	4020	40,7	99	80+	5000	2,40

* tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C

Available options:

- DALI Driver with DALI interface
- MW MW sensor
- OP Opal polycarbonate diffuser
- T830 Colour temperature 3000K, CRI 80+
- T840 Colour temperature 4000K, CRI 80+
- T850 Colour temperature 5000K, CRI 80+

