


CAELUM W LED

Anti-vandal Luminaires



Images for the product family and options:



Description: Wall-mounted anti-vandal LED luminaire
 Light distribution type: direct
 Optical system: opal polycarbonate diffuser, UV stable, vandal resistant, frame with stainless-steel security screws
 Housing: zinc coated steel
 Colour: white (RAL9010)

General data: Mains voltage: 220-240V, 0/50/60Hz
 LED lifetime, h: 100000/L80B50
 SDCM: 3
 Protection class IEC: I
 Ingress protection code: IP65
 Mechanical impact resistance: IK10+
 Protection symbol: D
 Glow wire test, °C: 850
 Operating temperature range, °C: ta -20...+40

Installation: On the wall (security bit to be ordered separately). Push-in terminal, 3x2x2.5mm²

Environment: Indoor/outdoor with roof


Application: Public place, underground passage, transport terminal, parking area, metro, prison, psychiatric hospital

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Caelum W LED1x1250 G544 T830 OP	380	110	150	1146	10,2	112	80+	3000	3,00
Caelum W LED1x1550 G545 T830 OP	380	110	150	1448	12,8	113	80+	3000	3,00
Caelum W LED1x1250 G544 T840 OP	380	110	150	1208	10,2	118	80+	4000	3,00
Caelum W LED1x1550 G545 T840 OP	380	110	150	1526	12,8	119	80+	4000	3,00

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

- DALI Driver with DALI interface and switch-control dimming
- MW Integrated microwave (MW) motion sensor with on-off control
- *note - in outdoor environment frequently moving objects (eg. trees, bushes, flags) can impact MW sensor operation*
- ASW(IP65) Integrated anti-vandal switch
- ASW(IP40) Integrated anti-vandal switch
- 1G Strain relief for power supply cable
- RAL RAL colour
- T830 Colour temperature 3000K, CRI 80+
- T840 Colour temperature 4000K, CRI 80+



Available accessories:



Product: Security bit ART9109 SP10
 Description: Security screw drill bit for 2-hole security fixings