


JETTA R LED

Recessed Luminaires



Description:	Recessed mounted decorative LED luminaire Light distribution type: indirect Optical system: white perforated steel louver with soft light distribution, opal polycarbonate film Housing: steel Colour: white (RAL9003)
General data:	Mains voltage: 220-240V, 0/50/60Hz LED lifetime, h: 100000/L80B50 SDCM: 3 Protection class IEC: I Ingress protection code: IP20 Mechanical impact resistance: IK02 Operating temperature range, °C: ta 0...+35
Installation:	In modular suspended ceilings (600/625), in ceilings with cut-out openings (mounting frame to be ordered separately). Push-in terminal, 3x2x2.5mm ²
Environment:	Indoor
Application:	Office, education, corridor, retail, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy, lm/W	CRI	CCT, K	Weight, kg
Jetta R LED1x2900 G359 T830	595	595	125	2746	25,3	108	80+	3000	3,75
Jetta R LED1x3700 G360 T830	595	595	125	3471	33,0	105	80+	3000	3,75
Jetta R LED1x4200 G361 T830	595	595	125	3980	38,3	104	80+	3000	3,75
Jetta R LED1x2900 G359 T840	595	595	125	2895	25,3	114	80+	4000	3,75
Jetta R LED1x3700 G360 T840	595	595	125	3658	33,0	111	80+	4000	3,75
Jetta R LED1x4200 G361 T840	595	595	125	4194	38,3	109	80+	4000	3,75

* Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

DALI	Driver with DALI interface and switch-control dimming	WIE3	3-pole "Wieland - gesis classic" type or compatible connector
BLT	Integrated wireless control unit and driver for lighting control via mobile device (via Bluetooth)	WIE4	4-pole "Wieland - gesis classic" type or compatible connector
COR	Driver with Corridor function (never off)	WIE5	5-pole "Wieland - gesis classic" type or compatible connector
COR1min	Driver with Corridor function 1min (switch off after 1 min.)	WIE5D	5-pole DALI "Wieland - gesis classic" type or compatible connector
COR30min	Driver with Corridor function 30min (switch off after 30 min.)	Schuko-1.5m	3-pole "Schuko" type plug with 3x1.0mm ² 1.5m cable
EM3	Emergency version 3 hours	Schuko-3.0m	3-pole "Schuko" type plug with 3x1.0mm ² 3.0m cable
EM3B	Emergency version 3 hours (best available technology)	SCREW	Gearbox cover fixed by screw
EM3A	Emergency version equipped with an autonomous testing system, 3 hours	T830	Colour temperature 3000K, CRI 80+
EM3D	Emergency version 3 hours with DALI interface	T840	Colour temperature 4000K, CRI 80+
1G	Strain relief for power supply cable		

Available accessories:



Product: Recessed MTG FRAME S626x626 RAL9003
Description: Frame for LED luminaire 595x595mm installation into plasterboard ceiling (1pcs), white steel

STANDARD

