



TECHNICAL DATA

Application	surrounding office buildings, parks, pedestrian
Colour	inox / graphite
Ingress protection	IP 66 for the optical part and the driver
Material	anodised aluminium alloy
Operating temperature range	from -40°C to +80°C
Expected useful lifetime	L90B10 - 100 000 h
CRI	>70
Input voltage frequency	50/60Hz
Power factor	≥0.95
Control system	LED lighting set has the possibility to connect to an external control system via DALI interface (optionally via analog signal 1-10V).
Concrete fixing / reinforcement basket	Ø 60 (311180) / 2-Ø0 (311206)



TABLE OF TYPES

Code	Symbol	Height of the column [m]	LED power	Luminaire power consumption	LED forward current	Colour temperature (CCT)	LEDs luminous flux*	Luminaire luminous flux*	Luminous efficacy*	Unit volume	Net weight
215530/1/A	FLEXI LED 24	4 m	24 W	28 W	1000 mA	2700 K	3300 lm	2250 lm	80 lm/W	0.6 m³	29 kg
215530/1/S	FLEXI LED 24	4 m	24 W	28 W	1000 mA	2700 K	3300 lm	2400 lm	86 lm/W	0.6 m³	29 kg
215530/3/A	FLEXI LED 24	4 m	24 W	28 W	1000 mA	3500 K	3400 lm	2350 lm	84 lm/W	0.6 m³	29 kg
215530/3/S	FLEXI LED 24	4 m	24 W	28 W	1000 mA	3500 K	3400 lm	2500 lm	89 lm/W	0.6 m³	29 kg
215530/4/A	FLEXI LED 24	4 m	24 W	28 W	1000 mA	4000 K	3900 lm	2650 lm	95 lm/W	0.6 m³	29 kg
215530/4/S	FLEXI LED 24	4 m	24 W	28 W	1000 mA	4000 K	3900 lm	2800 lm	102 lm/W	0.6 m³	29 kg
215530/6/A	FLEXI LED 24	4 m	24 W	28 W	1000 mA	5000 K	3900 lm	2650 lm	95 lm/W	0.6 m³	29 kg
215530/6/S	FLEXI LED 24	4 m	24 W	28 W	1000 mA	5000 K	3900 lm	2800 lm	102 lm/W	0.6 m³	29 kg
215533/1/A	FLEXI LED 48	5 m	48 W	55 W	1000 mA	2700 K	6600 lm	4500 lm	82 lm/W	0.75 m³	32 kg
215533/1/S	FLEXI LED 48	5 m	48 W	55 W	1000 mA	2700 K	6600 lm	4800 lm	87 lm/W	0.75 m³	32 kg
215533/3/A	FLEXI LED 48	5 m	48 W	55 W	1000 mA	3500 K	6900 lm	4700 lm	85 lm/W	0.75 m³	32 kg
215533/3/S	FLEXI LED 48	5 m	48 W	55 W	1000 mA	3500 K	6900 lm	5050 lm	92 lm/W	0.75 m³	32 kg
215533/4/A	FLEXI LED 48	5 m	48 W	55 W	1000 mA	4000 K	7800 lm	5300 lm	96 lm/W	0.75 m³	32 kg
215533/4/S	FLEXI LED 48	5 m	48 W	55 W	1000 mA	4000 K	7800 lm	5700 lm	104 lm/W	0.75 m³	32 kg
215533/6/A	FLEXI LED 48	5 m	48 W	55 W	1000 mA	5000 K	7800 lm	5300 lm	96 lm/W	0.75 m³	32 kg
215533/6/S	FLEXI LED 48	5 m	48 W	55 W	1000 mA	5000 K	7800 lm	5700 lm	104 lm/W	0.75 m³	32 kg

*) Tolerance +/- 5% due to LEDs accuracy

2) Symbol of chosen optical systemeg. 215530/3/A is FLEXI LED 24 3500K with A- asymmetric optical system

