



## TECHNICAL DATA

Anodising	10 colours
Diffuser	frosted (PMMA)
Application	surrounding office buildings, parks, pedestrian areas
Ingress protection	IP 65 for the optical part and the driver
Material	anodised aluminium alloy
Expected useful lifetime	150000 - 100000 h
CRI	>70
Input voltage frequency	50/60Hz
Number of LED	8



TABLE OF TYPES

Code	Symbol	Height of the columns [H]	LED power	Luminous power consumption	LED forward current	Colour temperature (CCT)	Luminous luminescence flux*	Luminous efficacy*	Concrete facing / reinforcement basket type	Diameter [Ø]	Net weight
452008/1/C.	KARIN 450 LED 8	455 mm	8 W	12 W	350 mA	2700 K	800 lm	80 lm/W	B-0 / Z-0	150 mm	3 kg
452008/3/C.	KARIN 450 LED 8	455 mm	8 W	12 W	350 mA	3000 K	850 lm	85 lm/W	B-0 / Z-0	150 mm	3 kg
452008/4/C.	KARIN 450 LED 8	455 mm	8 W	12 W	350 mA	4000 K	1000 lm	100 lm/W	B-0 / Z-0	150 mm	3 kg
452008/6/C.	KARIN 450 LED 8	455 mm	8 W	12 W	350 mA	5000 K	1000 lm	100 lm/W	B-0 / Z-0	150 mm	3 kg
45200/1/C.	KARIN 450 LED 16	455 mm	16 W	20 W	700 mA	2700 K	1600 lm	75 lm/W	B-0 / Z-0	150 mm	3 kg
45200/3/C.	KARIN 450 LED 16	455 mm	16 W	20 W	700 mA	3000 K	1650 lm	78 lm/W	B-0 / Z-0	150 mm	3 kg
45200/4/C.	KARIN 450 LED 16	455 mm	16 W	20 W	700 mA	4000 K	1850 lm	93 lm/W	B-0 / Z-0	150 mm	3 kg
45200/6/C.	KARIN 450 LED 16	455 mm	16 W	20 W	700 mA	5000 K	1850 lm	93 lm/W	B-0 / Z-0	150 mm	3 kg
452108/1/C.	KARIN 600 LED 8	575 mm	8 W	12 W	350 mA	2700 K	800 lm	80 lm/W	B-0 / Z-0	150 mm	3.5 kg
452108/3/C.	KARIN 600 LED 8	575 mm	8 W	12 W	350 mA	3000 K	850 lm	85 lm/W	B-0 / Z-0	150 mm	3.5 kg
452108/4/C.	KARIN 600 LED 8	575 mm	8 W	12 W	350 mA	4000 K	1000 lm	100 lm/W	B-0 / Z-0	150 mm	3.5 kg
452108/6/C.	KARIN 600 LED 8	575 mm	8 W	12 W	350 mA	5000 K	1000 lm	100 lm/W	B-0 / Z-0	150 mm	3.5 kg
45210/1/C.	KARIN 600 LED 16	575 mm	16 W	20 W	700 mA	2700 K	1600 lm	75 lm/W	B-0 / Z-0	150 mm	3.5 kg
45210/3/C.	KARIN 600 LED 16	575 mm	16 W	20 W	700 mA	3000 K	1650 lm	78 lm/W	B-0 / Z-0	150 mm	3.5 kg
45210/4/C.	KARIN 600 LED 16	575 mm	16 W	20 W	700 mA	4000 K	1850 lm	93 lm/W	B-0 / Z-0	150 mm	3.5 kg
45210/6/C.	KARIN 600 LED 16	575 mm	16 W	20 W	700 mA	5000 K	1850 lm	93 lm/W	B-0 / Z-0	150 mm	3.5 kg
45220/1/C.	KARIN 900 LED 8	875 mm	8 W	12 W	350 mA	2700 K	800 lm	80 lm/W	B-0 / Z-0	150 mm	4.2 kg
45220/3/C.	KARIN 900 LED 8	875 mm	8 W	12 W	350 mA	3000 K	850 lm	85 lm/W	B-0 / Z-0	150 mm	4.2 kg
45220/4/C.	KARIN 900 LED 8	875 mm	8 W	12 W	350 mA	4000 K	1000 lm	100 lm/W	B-0 / Z-0	150 mm	4.2 kg
45220/6/C.	KARIN 900 LED 8	875 mm	8 W	12 W	350 mA	5000 K	1000 lm	100 lm/W	B-0 / Z-0	150 mm	4.2 kg
45220/1/C.	KARIN 900 LED 16	875 mm	16 W	20 W	700 mA	2700 K	1600 lm	75 lm/W	B-0 / Z-0	150 mm	4.2 kg
45220/3/C.	KARIN 900 LED 16	875 mm	16 W	20 W	700 mA	3000 K	1650 lm	78 lm/W	B-0 / Z-0	150 mm	4.2 kg
45220/4/C.	KARIN 900 LED 16	875 mm	16 W	20 W	700 mA	4000 K	1850 lm	93 lm/W	B-0 / Z-0	150 mm	4.2 kg
45220/6/C.	KARIN 900 LED 16	875 mm	16 W	20 W	700 mA	5000 K	1850 lm	93 lm/W	B-0 / Z-0	150 mm	4.2 kg
45230/1/C.	KARIN 1200 LED 8	1175 mm	8 W	12 W	350 mA	2700 K	800 lm	80 lm/W	B-0/A-2/Z-6A	150 mm	5.5 kg
45230/3/C.	KARIN 1200 LED 8	1175 mm	8 W	12 W	350 mA	3000 K	850 lm	85 lm/W	B-0/A-2/Z-6A	150 mm	5.5 kg
45230/4/C.	KARIN 1200 LED 8	1175 mm	8 W	12 W	350 mA	4000 K	1000 lm	100 lm/W	B-0/A-2/Z-6A	150 mm	5.5 kg
45230/6/C.	KARIN 1200 LED 8	1175 mm	8 W	12 W	350 mA	5000 K	1000 lm	100 lm/W	B-0/A-2/Z-6A	150 mm	5.5 kg
45230/1/C.	KARIN 1200 LED 16	1175 mm	16 W	20 W	700 mA	2700 K	1600 lm	75 lm/W	B-0/A-2/Z-6A	150 mm	5.5 kg
45230/3/C.	KARIN 1200 LED 16	1175 mm	16 W	20 W	700 mA	3000 K	1650 lm	78 lm/W	B-0/A-2/Z-6A	150 mm	5.5 kg
45230/4/C.	KARIN 1200 LED 16	1175 mm	16 W	20 W	700 mA	4000 K	1850 lm	93 lm/W	B-0/A-2/Z-6A	150 mm	5.5 kg
45230/6/C.	KARIN 1200 LED 16	1175 mm	16 W	20 W	700 mA	5000 K	1850 lm	93 lm/W	B-0/A-2/Z-6A	150 mm	5.5 kg