

COSMO DELTA LED



Application: parks, parkings

Assembly: pole top mounted with $\varnothing 60 \times 85$ mm ending

Ingress protection: IP 66 for the optical part and the driver

Material: anodised aluminium alloy

Colour: inox / black

Optical system: PMMA optics, interchangeable LED module

Number of LEDs: 24

Operating temperature range: form -40°C to $+40^{\circ}\text{C}$

Expected useful lifetime: L90F10 – 50 000 h, L80F20 – 100 000 h

CRI: >70 for 5000K, 4000K; >80 for 3500K

Corrective factor S/P: 1,8 for 5000K; 1,45 for 3500K; 1,55 for 4000K

Input voltage frequency: 50 - 60Hz

Power factor: ≥ 0.95

Inrush current: : 43A / 260 μs

Luminaire COSMO DELTA LED has the possibility to connect to an external control system via DALI interface (optionally via analog signal 1- 10V).




Code	Symbol	LED power	Luminaire Power consumption	LED forward current	Colour temperature (CCT)	LEDs luminous flux ²⁾	Luminaire luminous flux ²⁾	Luminous efficacy	Unit volume	Luminaire net weight
2148032/3/... ¹⁾	COSMO DELTA LED 36	36W	44W	500mA	3500K	5 250lm	4750lm	108lm/W	0,32m ³	11kg
2148032/4/... ¹⁾	COSMO DELTA LED 36	36W	44W	500mA	4000K	5 850lm	4950lm	117lm/W	0,32m ³	11kg
2148032/6/... ¹⁾	COSMO DELTA LED 36	36W	44W	500mA	5000K	6 100lm	5150lm	117lm/W	0,32m ³	11kg
2148033/3/... ¹⁾	COSMO DELTA LED 48	48W	56W	700mA	3500K	7 000lm	6300lm	113lm/W	0,32m ³	11kg
2148033/4/... ¹⁾	COSMO DELTA LED 48	48W	56W	700mA	3500K	7 300lm	6600lm	118lm/W	0,32m ³	11kg
2148033/6/... ¹⁾	COSMO DELTA LED 48	48W	56W	700mA	5000K	8 150lm	6900lm	123lm/W	0,32m ³	11kg
2148035/3/... ¹⁾	COSMO DELTA LED 72	72W	80W	1000mA	3500K	9 400lm	8500lm	106lm/W	0,32m ³	11kg
2148035/4/... ¹⁾	COSMO DELTA LED 72	72W	80W	1000mA	4000K	10 450lm	8800lm	110lm/W	0,32m ³	11kg
2148035/6/... ¹⁾	COSMO DELTA LED 72	72W	80W	1000mA	5000K	10 950lm	9250lm	116lm/W	0,32m ³	11kg

1) Symbol of chosen optical system eg. **2148035/6/T2** is **COSMO DELTA LED 72 5000K with T2 optical system**


2) tolerance +/- 3% due to LEDs accuracy

Directive: 2014/35/UE (Official Journal of the UE L 96/357 29.03.2014), 2014/30/UE (Official Journal of the UE L 96/79 29.03.2014), 2011/65/UE, 2009/125/EC




COSMO DELTA LED


DW




ME




T2




T3




VS



SP



T4



Luminaire COSMO DELTA LED in standard has following functions of intelligent power supply:

- Connection to outside control system by DALI interface (operation of analog signal 1-10V as an option),
- Possibility of programming multistage dimming of luminaire, up to 5 intervals in the range of from 10 to 100% of nominal power,
- Temperature protection of LED module (from overheating) in case of unintentional luminaire operation during the,
- Regulation of power / luminous flux – the option of setting another value than the catalogue in the range of 30-100% of nominal one,

Acceptable quantity of luminaires COSMO DELTA LED on one circuit, protected by:

Overcurrent switches MCB type B or C

Luminaire	Typ	2A	4A	6A	10A	16A	20A	25A
COSMO DELTA LED 36, 48, 72W	B	0	1	3	6	10	12	15
	C	1	3	5	10	17	20	26

Fuse – type gG and GL

Luminaire	2A	4A	6A	10A	16A	20A	25A
COSMO DELTA LED 36, 48, 72W	2	6	9	17	27	34	43