





V315

LED spotlights

recessed round light fitting with electronic control gear • rotary to 355°, tipping to 90° • control gear option • passive cooling module • colour option • quality aluminium reflector • optional beam angle • protective glass or optional filter • suitable also for assembly in concrete housing



Order code	Pict.	Output	Flux	Tc	Ra	kg
V315sCWI.114/..	a	1 x 14 W	1400 lm	3000 K	≥ 80	1,2
V315sCCI.114/..	a	1 x 14 W	1450 lm	4000 K	≥ 80	1,2
V315sCDI.114/..	a	1 x 14 W	1450 lm	5000 K	≥ 80	1,2
V315sCWI.120/..	a	1 x 20 W	1950 lm	3000 K	≥ 80	1,2
V315sCCI.120/..	a	1 x 20 W	2050 lm	4000 K	≥ 80	1,2
V315sCDI.120/..	a	1 x 20 W	2050 lm	5000 K	≥ 80	1,2
V315sCWI.129/..	a	1 x 29 W	2650 lm	3000 K	≥ 80	1,2
V315sCCI.129/..	a	1 x 29 W	2800 lm	4000 K	≥ 80	1,2
V315sCDI.129/..	a	1 x 29 W	2800 lm	5000 K	≥ 80	1,2
V315sCWI.137/..	a	1 x 37 W	3600 lm	3000 K	≥ 80	1,2
V315sCCI.137/..	a	1 x 37 W	3800 lm	4000 K	≥ 80	1,2
V315sCDI.137/..	a	1 x 37 W	3800 lm	5000 K	≥ 80	1,2
V315sCWI.143/..	a	1 x 43 W	4100 lm	3000 K	≥ 80	1,2
V315sCCI.143/..	a	1 x 43 W	4300 lm	4000 K	≥ 80	1,2
V315sCDI.143/..	a	1 x 43 W	4300 lm	5000 K	≥ 80	1,2

Optional types of reflectors

10 / 32 / 45

Example of order code assembly: reflector with beam angle 32°

V315sCCI.120/32.S3

Color rendering index - CRI (only for Tc 3000K, 4000K)

D

Example of order code assembly: Ra ≥90

V315sDCI.120/32.S3

Dimmable version

A / D

Example of order code assembly: digital DALI

V315sCCD.120/32.S3

PDF Optional types of glasses / filters (1,5)

str. 256

T1 / T3 / F4 / F5 / F6 / F7 / FU / F1 / F2 / F3 / F8

Example of order code assembly: filter for pastry

V315sCWI.114/32F2.S3

PDF Accessories



ZPK
new



KZMK
new



KALK
new



KRP
new



LED COB

W3

S3

B3



230V-50Hz