


ANTLIA LED

Downlights



Description: Surface mounted LED downlight
Light distribution type: direct
Optical system: faceted aluminium reflector, 60°, low glare
Housing: aluminium
Colour: white, RAL9016

General data: Mains voltage: 220-240V, 50-60Hz
LED lifetime, h: 50000/L80B50 (75000/L80B50 low power versions)
SDCM: 3
Protection class IEC: I
Ingress protection code: IP20
Mechanical impact resistance: IK02
Operating temperature range, °C: ta 0...+35

Installation: On the ceiling. Push-in terminal, 3x2x2.5mm²

Environment: Indoor


Application: Office, education, hotel, corridor, bathroom, retail, showroom, exhibition, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Antlia LED1x1800 D342 T830	168	168	172	1734	13,5	128	80+	3000	1
Antlia LED1x2400 D343 T830	168	168	172	2312	19,8	117	80+	3000	1
Antlia LED1x3200 D344 T830	168	168	172	3063	26,7	115	80+	3000	1
Antlia LED1x1800 D342 T840	168	168	172	1788	13,5	132	80+	4000	1
Antlia LED1x2400 D343 T840	168	168	172	2382	19,8	120	80+	4000	1
Antlia LED1x3200 D344 T840	168	168	172	3153	26,7	118	80+	4000	1

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

- T830 Colour temperature 3000K, CRI 80+
- T840 Colour temperature 4000K, CRI 80+
- DALI Driver with DALI interface and switch-control dimming
- SUS Suspended version
- RAL RAL colour



Available accessories:



Product: Suspension MTG KIT SUSI
Description: Suspension wire set "I" type, 1.5m adjustable, 1pcs
**note - 1pcs MTG KIT SUSI for one fitting required*