


DELPHINUS LED

Spotlights



Images for the product family and options:



Description: Recessed mounted adjustable LED spotlight
 Light distribution type: direct
 Optical system: faceted aluminium reflector, 60°, tempered glass diffuser
 Housing: aluminium
 Colour: white (RAL 9016)

General data: Mains voltage: 220-240V, 0/50/60Hz
 LED lifetime, h: 50000/L80B50 (75000/L80B50 low power versions)
 SDCM: 3
 Protection class IEC: II
 Ingress protection code: IP40
 Mechanical impact resistance: IK02
 Operating temperature range, °C: ta 0...+35

Installation: In ceilings with cut-out openings (mounting brackets included). Push-in terminal, 2x1x1.5mm2

Environment: Indoor

Application: Retail, showroom, exhibition, public place



A spotlight ensures flexibility by adjusting luminaire according to your requirements

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Delphinus LED1x1700 D744 T830 R60	236	146	107	1623	13,8	118	80+	3000	2,50
Delphinus LED1x2300 D745 T830 R60	236	146	107	2252	19,1	118	80+	3000	2,50
Delphinus LED1x3100 D746 T830 R60	236	146	107	3037	27,5	111	80+	3000	2,50
Delphinus LED1x4550 D787 T830 R60	236	146	107	4443	40,9	109	80+	3000	2,50
Delphinus LED1x5250 D747 T830 R60	236	146	107	5139	47,7	108	80+	3000	2,50
Delphinus LED1x1700 D744 T840 R60	236	146	107	1663	13,8	121	80+	4000	2,50
Delphinus LED1x2300 D745 T840 R60	236	146	107	2309	19,1	121	80+	4000	2,50
Delphinus LED1x3100 D746 T840 R60	236	146	107	3115	27,5	113	80+	4000	2,50
Delphinus LED1x4550 D787 T840 R60	236	146	107	4559	40,9	112	80+	4000	2,50
Delphinus LED1x5250 D747 T840 R60	236	146	107	5238	47,7	110	80+	4000	2,50
Delphinus LED1x1700 D744 T930 R60	236	146	107	1328	13,3	100	90+	3000	2,50
Delphinus LED1x2300 D745 T930 R60	236	146	107	1860	18,4	101	90+	3000	2,50
Delphinus LED1x3100 D746 T930 R60	236	146	107	2540	26,3	97	90+	3000	2,50
Delphinus LED1x4550 D787 T930 R60	236	146	107	3657	41,0	89	90+	3000	2,50
Delphinus LED1x5250 D747 T930 R60	236	146	107	4110	47,6	86	90+	3000	2,50

TECHNICAL DATA SHEET

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Delphinus LED1x1700 D744 T940 R60	236	146	107	1419	13,3	107	90+	4000	2,50
Delphinus LED1x2300 D745 T940 R60	236	146	107	1988	18,4	108	90+	4000	2,50
Delphinus LED1x3100 D746 T940 R60	236	146	107	2715	26,3	103	90+	4000	2,50
Delphinus LED1x4550 D787 T940 R60	236	146	107	3909	41,0	95	90+	4000	2,50
Delphinus LED1x5250 D747 T940 R60	236	146	107	4393	47,6	92	90+	4000	2,50

* Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

DALI	Driver with DALI interface and switch-control dimming	Europlug-3.0m	2-pole "Europlug" type plug with 2x1.0mm ² 3.0m cable
WIE3-0.5m	3-pole "Wieland - gesis classic" type or compatible connector with 0.5m cable	T830	Colour temperature 3000K, CRI 80+
WIE5D-0.5m	5-pole DALI "Wieland - gesis classic" type or compatible connector with 0.5m cable	T840	Colour temperature 4000K, CRI 80+
Europlug-1.5m	2-pole "Europlug" type plug with 2x1.0mm ² 1.5m cable	T930	Colour temperature 3000K, CRI 90+
		T940	Colour temperature 4000K, CRI 90+

STANDARD

