

Narvik



Colour:




Colour temperature:

2700K 4000K



Luminaire suitable for extreme conditions.



Fully replaceable electrical kit.



Vandal-resistant luminaire.




Energy under control (mainly energy-saving solutions - control, dimming, motion-dusk sensor).

Accessories:


Art. 505

Concreting anchor



Art. 110

Ground anchor





Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
557AL	LED	21.8W	556lm	3000K	> 110 000h	-
557GR						-
5091AL		22.5W	597lm			DALI2/ NightDim
5091GR						
5024GR		21.8W	564lm	4000K	> 50 000h	-
5024GR						-
5090GR			582lm			DALI2/ NightDim
5090GR						



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control			
1735AL	LED	22.2W	1122lm	3000K	> 72 000h	DALI2/ NightDim			
1735GR						-			
1850AL						13.4W	666lm	4000K	DIM
1850GR									
559AL		757lm	DALI2/ NightDim						
559GR				-					
1733AL		22.2W		1162lm	4000K	-			
1733GR							-		
1737AL			-						
1737GR			-						
1851AL		-							
1851GR		-							



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control			
1736AL	LED	22.2W	1416lm	3000K	> 72 000h	DALI2/ NightDim			
1736GR						-			
1852GR						13.6W	853lm	4000K	DIM
1852GR									
553AL		959lm	DALI2/ NightDim						
553GR				-					
1734AL		22.2W		1475lm	4000K	-			
1734GR							-		
1738AL			-						
1738GR			-						
1853AL		-							
1853GR		-							