

Quantum

LED Quantum light body

Registered patent



Quantum masks



NEW MASKS IN GLASS



Quantum is a new range of recessed lighting fittings for outdoors planned to contain very efficient power leds. A new innovative concept offering significative options.

Small size: the light body, small and shallow, as result of a careful design of miniature shape, contains a well dimensioned thermic heat sink and the transformer 220-250 V / 12V. It allows to install Quantum in a normal and easy 220-250V power line. The backboxes are small and shallow as well.

Maximum modularity: you can achieve the final look covering the light body with a wide range of masks in polycarbonate, aluminium different colors, or in matt finish stainless steel 316 L. The new masks in glass make Quantum more decorative and elegant.

Different angle beam available: the light body shapes offer many types of lighting distributions and permit to choose the best light for your environment.

Power led performance: this range utilizes very efficient leds, especially dedicated to the habitat areas: very good color rendering index (85), 3,2 and 4,2 W for 410 lumen, and 50.000 h life.

Small and elegant garden posts complete the range. A first light is directed towards down to give light on the walkway plane and an second optional light in the opposite side can enlarge the lighting area in the other side of the post.

LED Quantum posts



Quantum. New recessed lighting technology.


Easy and practical to install: the light body can be dressed by different types of Masks.



Six light bodies in different shapes, driver 220-240V inside, **can be connected to the normal 220-240V power line** (or 12V on request). Complete the lighting fitting and dress the body with Masks in the material you'll think right: the precious stainless steel 316 L, the aluminium in three different colors, the more economical polycarbonate or precious glass.

The right light.

The inclined light shapes are made to push the light towards the ground: not to lose any lumen and to avoid any dazzling. The vertical versions distribute forward the light, the horizontal versions enlarge the angle beam and allow to increase the spacing between two lamps.



Power led efficiency.


Last generation power led. Be sure the light will be enough.

| Watt | Lumen | Tonality | CRI - Color rendering index |
|------|-------|----------|-----------------------------|
| 1 | 105 | 3500K | 85 |
| 3,2 | 265 | 3500K | 85 |
| 4,2 | 410 | 3500K | 85 |















Photobiologic safety: risk group 0 standard EN 62471:08.

Small sizes: a great asset.


Inside a powerful heat sink keeps the temperature in the correct limit and the 220V-250V / 12V transformer allows to use a normal power line. 49 mm only inside in the wall.



Maximum modularity: a good match for the right choice.

| Light bodies | Backboxes | Masks | | | | | | | Materials | |
|---|---|---|---|---|---|--|---|---|-----------------|-----------------|
| |  |  |  |  |  |  |  |  | | |
| 1 W  | 4 MOD. | ■ | | | | | | | Polycarbonate | |
| | | ■ | | | | | | | Aluminium | |
| | | ■ | | | | | | | Stainless steel | |
| | | ■ | | | | | | | Glass | |
| 3,2 W  | 4 MOD. | ■ | | | | | | | Polycarbonate | |
| | | ■ | | | | | | | Aluminium | |
| | | ■ | | | | | | | Stainless steel | |
| | | ■ | | | | | | | Glass | |
| 1 W  | 3 MOD. | | ■ | | | | | | Polycarbonate | |
| | | | | | | | | | Aluminium | |
| | | | | | | | | | Stainless steel | |
| | | | ■ | | | | | | Glass | |
| 3,2 W  | 4 MOD. | | | ■ | | | | | Polycarbonate | |
| | | | | | ■ | | | | Aluminium | |
| | | | | | | ■ | | | Stainless steel | |
| | | | | | | | ■ | | Glass | |
| 4,2 W  | 6 MOD. | | | | | ■ | | | Polycarbonate | |
| | | | | | | | ■ | | Aluminium | |
| | | | | | | | | ■ | Stainless steel | |
| | | | | | | | | | ■ | Glass |
| 4,2 W  | 6 MOD. | | | | | | ■ | | Polycarbonate | |
| | | | | | | | | ■ | ■ | Aluminium |
| | | | | | | | | ■ | ■ | Stainless steel |
| | | | | | | | | | | ■ |

The garden post. Elegant and flexible.





The range Quantum is complete with a small and elegant garden post in aluminium or matt stainless steel 316 L. Thanks to the body 5421 or 5425 the basic light is downwards to illuminate on your walkway, but on the opposite side is possible an optional second light directed forward. A new garden post in aluminium allows to drive the light towards the ground to avoid any dazzling.





- Body in polycarbonate
- Stainless steel screws
- To be installed on the backbox cod. 5481
- Photobiologic safety: risk group 0 standard EN 62471:08
- Led 1 W incorporated
- 105 lumen
- Warm tonality 3.500K / CRI color rendering index 85
- Life: 70% guaranteed after 50.000 h / progressive reduction until a max of 100.000 h
- 220-250V power / 350 mA - 12V incorporated
- IP 65 with 5481 - Class II double insulation
- Made according to EN 60598-1:08+A11:09 European standards C €





| CODE NO. | Lamp | W | Lumen | A | B | C |
|-------------|-------|---|-------|----|-----|----|
| 5421 | □ Led | 1 | 105 | 70 | 130 | 49 |

12V version on request. IP65 range is guaranteed if installed with Goccia backbox code 5481. Other tonality on request.



- Body in polycarbonate
- Stainless steel screws
- To be installed on the backbox cod. 5481
- Photobiologic safety: risk group 0 standard EN 62471:08
- Led Citizen 3,2 W incorporated
- 265 lumen totally
- Warm tonality 3.500K / CRI color rendering index 85
- Life: 70% guaranteed after 50.000 h / progressive reduction until a max of 100.000 h
- 220-250V power / 350 mA - 12V incorporated
- IP 65 with 5481 - Class II double insulation
- Made according to EN 60598-1:08+A11:09 European standards C €




| CODE NO. | Lamp | W | Lumen | A | B | C |
|-------------|-------|-----|-------|----|-----|----|
| 5425 | □ Led | 3,2 | 265 | 70 | 130 | 49 |

12V version on request. Dimmable version on request. IP65 range is guaranteed if installed with Goccia backbox code 5481. Other tonality on request.



- Body in polycarbonate
- Stainless steel screws
- To be installed on the backbox cod. 5480
- Photobiologic safety: risk group 0 standard EN 62471:08
- Led Citizen 1 W incorporated
- 105 lumen
- Warm tonality 3.500K / CRI color rendering index 85
- Life: 70% guaranteed after 50.000 h / progressive reduction until a max of 100.000 h
- 220-250V power / 350 mA - 12V incorporated
- IP 65 with 5480 - Class II double insulation
- Made according to EN 60598-1:08+A11:09 European standards C €




| CODE NO. | Lamp | W | Lumen | A | B | C |
|-------------|-------|---|-------|-----|----|----|
| 5420 | □ Led | 1 | 105 | 109 | 70 | 49 |

12V version on request. IP65 range is guaranteed if installed with Goccia backbox code 5480. Other tonality on request.



- Body in polycarbonate
- Stainless steel screws
- To be installed on the backbox cod. 5481
- Photobiologic safety: risk group 0 standard EN 62471:08
- Led Citizen 3,2 W incorporated
- 265 lumen totally
- Warm tonality 3.500K / CRI color rendering index 85
- Life: 70% guaranteed after 50.000 h / progressive reduction until a max of 100.000 h
- 220-250V power / 350 mA - 12V incorporated
- IP 65 with 5481 - Class II double insulation
- Made according to EN 60598-1:08+A11:09 European standards C E




| CODE NO. | Lamp | W | Lumen | A | B | C |
|----------|---------|-----|-------|-----|----|----|
| 5430 | ☐ ☐ Led | 3,2 | 265 | 130 | 70 | 49 |

12V version on request. Dimmable version on request.
IP65 range is guaranteed if installed with Goccia backbox code 5481.
Other tonality on request.



- Body in polycarbonate
- Stainless steel screws
- To be installed on the backbox cod. 5482
- Photobiologic safety: risk group 0 standard EN 62471:08
- 57 Led Citizen 4,2 W incorporated
- 410 lumen totally
- Warm tonality 3.500K / CRI color rendering index 85
- Life: 70% guaranteed after 50.000 h / progressive reduction until a max of 100.000 h
- 220-250V power / 350 mA - 12V incorporated
- IP 65 with 5482 - Class II double insulation
- Made according to EN 60598-1:08+A11:09 European standards C E





| CODE NO. | Lamp | W | Lumen | A | B | C |
|----------|------------------|-----|-------|-----|----|----|
| 5435 | ☐ ☐☐☐☐☐☐☐☐☐☐ Led | 4,2 | 410 | 186 | 70 | 50 |

12V version on request. Dimmable version on request.
IP65 range is guaranteed if installed with Goccia backbox code 5482.




- Id. code 5435





| CODE NO. | Lamp | W | Lumen | A | B | C |
|----------|------------------|-----|-------|-----|----|----|
| 5440 | ☐ ☐☐☐☐☐☐☐☐☐☐ Led | 4,2 | 410 | 186 | 70 | 50 |

12V version on request. Dimmable version on request.
IP65 range is guaranteed if installed with Goccia backbox code 5482.








- Backbox in technopolimer
- Cover included



| CODE NO. | Description | A | B | C |
|-------------|-----------------------|-----|----|----|
| 5480 | Backbox for body 5420 | 122 | 84 | 56 |





- Backbox in technopolimer
- Cover included



| CODE NO. | Description | A | B | C |
|-------------|-----------------------------------|-----|----|----|
| 5481 | Backbox for bodies 5421-5425-5430 | 145 | 84 | 56 |



- Backbox in technopolimer
- Cover included



| CODE NO. | Description | A | B | C |
|-------------|------------------------------|-----|----|----|
| 5482 | Backbox for bodies 5435-5440 | 200 | 84 | 56 |

Quantum dichroic filters




- Lighting filters

Colours **AR** **VE** **BL**


| CODE NO. | Description |
|---------------|--------------------------------------|
| 5483 * | Dichroic filter for bodies 5420 |
| 5484 * | Dichroic filter for bodies 5421-5425 |
| 5485 * | Dichroic filter for bodies 5430 |
| 5486 * | Dichroic filter for bodies 5435 |
| 5487 * | Dichroic filter for bodies 5440 |

- Covering masks in polycarbonate
- Snap fastener + security screws




Colours **GR**


| CODE NO. | Description | A | B | C |
|---------------|------------------------|-----|----|-----|
| 5452 * | Mask for 5421 and 5425 | 134 | 74 | 6,5 |



| CODE NO. | Description | A | B | C |
|---------------|---------------|-----|----|-----|
| 5453 * | Mask for 5430 | 134 | 74 | 6,5 |




| CODE NO. | Description | A | B | C |
|---------------|---------------|-----|----|-----|
| 5454 * | Mask for 5435 | 190 | 74 | 6,5 |




| CODE NO. | Description | A | B | C |
|---------------|---------------|-----|----|-----|
| 5455 * | Mask for 5440 | 190 | 74 | 6,5 |

- Covering masks in die-cast aluminium
- Snap fastener + security screws
- Pre-phosphochromed UV resistant painting
- Corten colour available upon request




Colours **GR** **GM** **BI**


| CODE NO. | Description | A | B | C |
|---------------|-------------------------------|-----|----|-----|
| 5422 * | Mask for bodies 5421 and 5425 | 134 | 74 | 6,5 |




| CODE NO. | Description | A | B | C |
|---------------|--------------------|-----|----|-----|
| 5460 * | Mask for body 5420 | 109 | 74 | 6,5 |




| CODE NO. | Description | A | B | C |
|---------------|--------------------|-----|----|-----|
| 5463 * | Mask for body 5430 | 134 | 74 | 6,5 |




| CODE NO. | Description | A | B | C |
|---------------|--------------------|-----|----|-----|
| 5464 * | Mask for body 5435 | 190 | 74 | 6,5 |



| CODE NO. | Description | A | B | C |
|---------------|--------------------|-----|----|-----|
| 5465 * | Mask for body 5440 | 190 | 74 | 6,5 |




| CODE NO. | Description | A | B | C |
|---------------|--------------------|----|-----|-----|
| 5466 * | Mask for body 5440 | 74 | 190 | 6,5 |



| CODE NO. | Description | A | B | C |
|---------------|--------------------|-----|----|-----|
| 5467 * | Mask for body 5440 | 190 | 74 | 6,5 |




- Covering masks in stainless steel 316 L
- Snap fastener + security screws
- Brushed and satin matt surface




Colours **IN**


| CODE NO. | Description | A | B | C |
|---------------|-------------------------------|-----|----|-----|
| 5472 * | Mask for bodies 5421 and 5425 | 137 | 77 | 7,5 |




| CODE NO. | Description | A | B | C |
|---------------|--------------------|-----|----|-----|
| 5473 * | Mask for body 5430 | 137 | 77 | 7,5 |




| CODE NO. | Description | A | B | C |
|---------------|--------------------|-----|----|-----|
| 5474 * | Mask for body 5435 | 193 | 77 | 7,5 |



| CODE NO. | Description | A | B | C |
|---------------|--------------------|-----|----|-----|
| 5475 * | Mask for body 5440 | 193 | 77 | 7,5 |




| CODE NO. | Description | A | B | C |
|---------------|--------------------|----|-----|------|
| 5476 * | Mask for body 5440 | 77 | 193 | 10,5 |



| CODE NO. | Description | A | B | C |
|---------------|--------------------|-----|----|------|
| 5477 * | Mask for body 5440 | 193 | 77 | 10,5 |




- Covering masks in flat tempered glass
- Snap fastener - no security screws
- Opal finish on the glass and inclined plan in white




Colours **OP**


| CODE NO. | Description | A | B | C |
|---------------|-------------------------------|-----|----|----|
| 5441 * | Mask for bodies 5421 and 5425 | 138 | 78 | 10 |



| CODE NO. | Description | A | B | C |
|---------------|--------------------|----|-----|----|
| 5442 * | Mask for body 5420 | 78 | 114 | 10 |



| CODE NO. | Description | A | B | C |
|---------------|--------------------|----|-----|----|
| 5443 * | Mask for body 5430 | 78 | 138 | 10 |




| CODE NO. | Description | A | B | C |
|---------------|--------------------|----|-----|-----|
| 5444 * | Mask for body 5435 | 78 | 194 | 9,7 |

Quantum external box aluminium

goccia
ILLUMINAZIONE




- Aluminium body
- Made to contain body 5430, 5435 or 5440 and its masks
- Rear or side cable entry
- Through wiring allowed
- Terminal block incorporated
- Suitable to 14 mm \varnothing wiring
- Pre-phosphochrome + UV resistant coating
- Made according to EN 60439-1 European standards $\text{C}\ \text{C}\ \text{C}$




Colours **GR** **GM**

| CODE NO. | Description | A | B | C |
|---------------|------------------------------|--------|-------|----|
| 5411 * | Box for body 5430 | 143 | 82 | 76 |
| 5412 * | Box for bodies 5435 and 5440 | 197,65 | 80,65 | 76 |

Box only. Quantum fitting supplied separately.



Box + 5430-5435 downwards oriented.




Box + 5440 outwards oriented.

Quantum wall washer box aluminium




- Aluminium body
- Made to contain body 5430, 5435 or 5440 and its masks
- The body 5435 can be outwards or wallwards oriented
- Rear or side cable entry
- Through wiring allowed
- Terminal block incorporated
- Suitable to 12 mm \varnothing wiring
- Pre-phosphochrome + UV resistant coating
- Made according to EN 60439-1 European standards $\text{C}\ \text{C}\ \text{C}$




Colours **GR** **GM**

| CODE NO. | Description | A | B | C |
|---------------|------------------------------|--------|--------|----|
| 5415 * | Box for body 5430 | 138,89 | 112,95 | 56 |
| 5416 * | Box for bodies 5435 and 5440 | 194,89 | 112,95 | 56 |

Box only. Quantum fitting supplied separately.




Box + 5430-5435 outwards/wallwards oriented.





Box + 5440 downwards oriented.

Only one light point will generate all the lights you need



The vandal-proof cable trunking, completely in aluminium, allows to give power to many lights starting from only one light point. Suitable to hold the external or the wall-washer boxes. In this way you can bring the light where you cannot recess a backbox or where the wall already is existing.






- Holding bar in extruded aluminium
- Vandal proof aluminium conduit
- Bar + conduit suitable to be cut
- 10 cable-holding clips inside
- Snapping connection bar/conduit
- IK10 (20 joules) impact test
- Pre-phosphochrome + UV resistant coating
- Made according to EN 60439-1 European standards CE


Colours **GR** **GM**

| CODE NO. | Description | A | B | C |
|----------|---------------|------|------|-------|
| 5401 * | Bar + conduit | 25,5 | 2000 | 39,92 |




Connection bracket

- Steel bracket to connect two conduits
- Made in unpainted steel




| CODE NO. | Description | A | B | C |
|----------|--------------------|----|---|----|
| 5402 | Connection bracket | 22 | 4 | 54 |




Cable entry connection

- Pair of connections in aluminium
- To cover cable entry




Colours **GR** **GM**

| CODE NO. | Description | A | B | C |
|----------|-------------------------------|----|-------|-------|
| 5405 * | Connection pair for 5411-5412 | 35 | 40,13 | 39,92 |
| 5406 * | Connection pair for 5415-5416 | 35 | 32,13 | 39,92 |



Side cap

- Rubber side cap







| CODE NO. | Description | A | B | C |
|----------|-------------|------|---|------|
| 5407 | Side cap | 24,5 | 8 | 38,8 |

Quantum aluminium post

goccia
ILLUMINAZIONE



- Structure, base and top in aluminium
- Complete with Led 3,2W / 3500K / CRI 85 / 265 lumen + mask 5462
- Option to insert on the back the body 5440 and the mask 5465 or 5466
- Driver 230V inside
- Connection box inside
- Photobiologic safety: risk group 0 standard EN 62471:08
- Pre-phosphochrome + UV resistant coating
- Corten colour available upon request
- IP 65  - Class II 
- Made according to EN 60439-1 European standards 






Colours **GR** **GM**


| CODE NO. | Lamp | W | Lumen | A | B | C |
|---------------|---|-----|-------|-----|------|----|
| 5591 * |  Led | 3,2 | 265 | 495 | 86,5 | 93 |

Complete with Led body in front.

Quantum stainless steel post




- Structure in stainless steel 316 L
- Complete with Led 3,2W / 3500K / CRI 85 / 265 lumen + mask 5472
- Option to insert on the back the body 5440 and the mask 5475 or 5476
- Driver 230V inside
- Connection box inside
- Photobiologic safety: risk group 0 standard EN 62471:08
- Brushed and satin matt surface
- IP 65  - Class II 
- Made according to EN 60439-1 European standards 




Colours **IN**

| CODE NO. | Lamp | W | Lumen | A | B | C |
|---------------|---|-----|-------|-----|----|-----|
| 5592 * |  Led | 3,2 | 265 | 495 | 66 | 100 |

Complete with Led body in front.



Quantum post. One light.




Quantum post. Two lights.



Quantum plate with anchoring set



- Stainless steel plate with ground anchoring set
- To be installed with codes 5591 - 5592




| CODE NO. | Description | A | B | C |
|-------------|--------------------------|----|----|-----|
| 5496 | Plate with anchoring set | 92 | 77 | 200 |

Energy class: go to code index

Quantum aluminium post



- Structure, base and top in aluminium
- Complete with Led 10W / 3500K / CRI 85 / 1040 lumen + mask
- Driver 230V inside
- Connection box inside
- Photobiologic safety: risk group 0 standard EN 62471:08
- Pre-phosphochrome + UV resistant coating
- Corten colour available upon request
- IP 65 - Class II
- Made according to EN 60439-1 European standards





Colours **GR** **GM**



| CODE NO. | Lamp | W | Lumen | A | B | C |
|---------------|------|----|-------|-----|-----|-----|
| 5593 * | Led | 10 | 1040 | 825 | 194 | 164 |
| 5594 * | Led | 10 | 1040 | 530 | 164 | |


Complete with 10W Led. Driver 230V inside.



Quantum plate with anchoring set



- Stainless steel plate with ground anchoring set
- To be installed with codes 5593-5594




| CODE NO. | Description | A | B | C |
|-------------|--------------------------|-----|-----|-----|
| 5497 | Plate with anchoring set | 195 | 160 | 200 |

Quantum small garden post

goccia
ILLUMINAZIONE




- Structure totally in aluminium
- Complete with Led 3,2W (5595) and 4,2W (5596). Mask included
- Side and bottom cable entry
- CRI 85 / 3500K
- Driver 230V inside
- Through wiring allowed
- Pre-phosphochrome + UV resistant coating
- Corten colour available upon request
- IP 65 - Class II
- Made according to EN 60439-1 European standards



Colours **GR** **GM**

| CODE NO. | Lamp | W | Lumen | A | B | C |
|---------------|------|-----|-------|-----|-----|----|
| 5595 * | Led | 3,2 | 265 | 139 | 110 | 56 |
| 5596 * | Led | 4,2 | 410 | 195 | 110 | 56 |


Complete with Led unit 3,2W (5595) and 4,2W (5596).



Quantum small garden post



- Structure totally in aluminium
- Complete with Led 4,2W. Mask included
- Side and bottom cable entry
- CRI 85 / 3500K
- Driver 230V inside
- Through wiring allowed
- Pre-phosphochrome + UV resistant coating
- Corten colour available upon request
- IP 65 - Class II
- Made according to EN 60439-1 European standards



Colours **GR** **GM**

| CODE NO. | Lamp | W | Lumen | A | B | C |
|---------------|------|-----|-------|-----|-----|----|
| 5598 * | Led | 4,2 | 410 | 195 | 110 | 56 |

Complete with Led unit 4,2W.

