

Asker Bollard




Colour:

- Graphite
- Aluminium
- Black

Colour temperature:

2700K 4000K



Fully replaceable electrical kit.




Energy under control (mainly energy-saving solutions - control, dimming, motion-dusk sensor).

Accessories:


Art. 1907

Concreting anchor



Art. 1908

Ground anchor





Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens	IK										
1311AL	LED	9,5W	585lm	3000K	50 000h	-	-	IK10										
1311BL																		
1311GR		7,7W	697lm		3000K	> 109 000h	Dimmable	IESNA type II/III	IK08									
1314AL																		
1314BL																		
1314GR																		
1315AL																		
1315BL																		
1315GR																		
1316AL																		
1316BL																		
1316GR																		
1317AL		7,8W	599lm		3000K	> 109 000h	DALI2	IESNA type V	IK08									
1317BL																		
1317GR																		
1318AL										7,7W	724lm	4000K	> 109 000h	Dimmable	IESNA type II/III	IK08		
1318BL																		
1318GR																		
1319AL																		
1319BL																		
1319GR																		
1320AL	7,7W			617lm													4000K	> 109 000h
1320BL																		
1320GR																		
1322AL																		
1322BL																		
1322GR																		
5210AL		10W	394lm		3000K	> 55 000h	Dimmable	-	IK10									
5210BL																		
5210GR			457lm		4000K					> 55 000h	Dimmable	-	IK10					
5211AL																		
5211BL																		
5211GR																		



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Motion Detector		
1338AL	LED	9,7W	585lm	3000K	50 000h	PIR		
1338BL								
1338GR			640lm	4000K			50 000h	PIR
1339AL								
1339BL								
1339GR								



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens	IK
1310AL	LED	9,5W	585lm	3000K	50 000h	On/Off		IK10
1310BL				4000K				
1310GR								
5120AL								
5120BL			636lm	4000K				
5120GR								
5212AL		10W	394lm	3000K	> 55 000h	Dimmable	IESNA type II/III	IK08
5212BL				4000K				
5212GR								
5213AL								
5213BL			458lm	4000K				
5213GR								
5214AL		7,7W	682lm	3000K	>109 000h	Dimmable	IESNA type V	IK08
5214BL				4000K				
5214GR								
5215AL								
5215BL			654lm	4000K				
5215GR								
5216AL			604lm	3000K				
5216BL				4000K				
5216GR								
5217AL								
5217BL								
5217GR								



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Motion Detector
1336AL	LED	9,7W	585lm	3000K	50 000h	PIR
1336BL				4000K		
1336GR						
1337AL						
1337BL			636lm	4000K		
1337GR						