

Namsos



Colour:



Aluminium



Graphite


Colour temperature:

2700K

4000K



Luminaire suitable for extreme conditions.



Fully replaceable electrical kit.




Energy under control (mainly energy-saving solutions – control, dimming, motion-dusk sensor).

Accessories:


Art. 112

Concreting anchor




Art. 113

Ground anchor



Art. 114

Anchoring support





Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	
1931AL	LED	8,4W	566lm	3000K	> 102 000h	Dimmable	
1931GR							
5012AL		8,6W	612lm	4000K			DALI2
5012GR							
6035AL		13,8W	877lm	4000K		DALI2	
6035GR							
6033AL		13,8W	904lm	3000K			DALI2
6033GR							
1921AL		13,6W	843lm	3000K		DALI2	
1921GR							
1922AL		14W	907lm	4000K			DALI2
1922GR							



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	
1932AL	LED	8,6W	566lm	3000K	> 102 000h	Dimmable	
1932GR							
5013AL		8,6W	612lm	4000K			DALI2
5013GR							
6036AL		13,8W	877lm	4000K		DALI2	
6036GR							
6034AL		13,8W	904lm	3000K			DALI2
6034GR							
1923AL		13,6W	843lm	3000K		DALI2	
1923GR							
1924AL		14W	907lm	4000K			DALI2
1924GR							

