


CORONA Q LED

Recessed Luminaires



Description:	Recessed mounted decorative LED luminaire Light distribution type: direct Optical system: low glare matt micro-prismatic (DPRZ LT80) or high transmission opal (OP LT80) diffuser, PMMA Housing: steel Colour: white (RAL9003)
General data:	Mains voltage: 220-240V, 50-60Hz LED lifetime, h: 100000/L80B50 SDCM: 3 Protection class IEC: I Ingress protection code: IP40/20 Mechanical impact resistance: IK05 Operating temperature range, °C: ta 0...+35
Installation:	In modular suspended ceilings (600/625), in ceilings with cut-out openings (mounting frame to be ordered separately). Push-in terminal, 3x2x2.5mm ²
Environment:	Indoor
Application:	Office, education, corridor, retail, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy, lm/W	CRI* (Ra)	CCT*, K	Weight, kg
Corona Q LED1x3250 E394 T830 OP LT80	595	595	70	3096	30,0	103	80+	3000	5,00
Corona Q LED1x4550 E395 T830 OP LT80	595	595	70	4334	43,9	99	80+	3000	5,00
Corona Q LED1x6500 E396 T830 OP LT80	595	595	70	6195	58,9	105	80+	3000	5,00
Corona Q LED1x3250 E394 T840 OP LT80	595	595	70	3234	30,0	108	80+	4000	5,00
Corona Q LED1x4550 E395 T840 OP LT80	595	595	70	4542	43,9	103	80+	4000	5,00
Corona Q LED1x6500 E396 T840 OP LT80	595	595	70	6492	58,9	110	80+	4000	5,00
Corona Q LED1x2950 E394 T830 DPRZ LT80	595	595	70	2795	30,0	93	80+	3000	5,00
Corona Q LED1x4100 E395 T830 DPRZ LT80	595	595	70	3913	43,9	89	80+	3000	5,00
Corona Q LED1x5900 E396 T830 DPRZ LT80	595	595	70	5593	58,9	95	80+	3000	5,00
Corona Q LED1x2950 E394 T840 DPRZ LT80	595	595	70	2920	30,0	97	80+	4000	5,00
Corona Q LED1x4100 E395 T840 DPRZ LT80	595	595	70	4100	43,9	93	80+	4000	5,00
Corona Q LED1x5900 E396 T840 DPRZ LT80	595	595	70	5860	58,9	99	80+	4000	5,00

* Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification


TECHNICAL DATA SHEET

Available options:


DALI Driver with DALI interface and switch-control dimming
 EAIRB-M Master luminaire with integrated smart sensor and driver with wireless communication and grouping possibilities for lighting control
 EAIRB-S Slave luminaire with integrated EAIRB type driver for lighting control
 *note - max system size 1x EAIRB-M + 3x EAIRB-S
 *note - max wire length from EAIRB-M to last EAIRB-S - 11 meters
 ACT+ Integrated self-learning sensor and driver for lighting control
 BLT Integrated wireless control unit and driver for lighting control via mobile device (via Bluetooth)
 TW Integrated light source and driver for Tunable white control 2700-6500 K
 BLT TW Integrated light source, wireless control unit and driver for Tunable white control 2700-6500 K via mobile device (via Bluetooth)
 *note - ask for special model with options: TW and BLT TW
 DLIGHT Integrated daylight sensor and dimming driver for simple setting of constant light level
 *note - ask for compatibility details
 COR Driver with Corridor function (never off)
 COR1min Driver with Corridor function 1min (switch off after 1 min.)
 COR30min Driver with Corridor function 30min (switch off after 30 min.)
 MW Integrated microwave (MW) motion sensor with on-off control
 *note - some shadows might be visible with MW option

EM3 Emergency version 3 hours
 EM3B Emergency version 3 hours (best available technology)
 EM3A Emergency version equipped with an autonomous testing system, 3 hours
 EM3D Emergency version 3 hours with DALI interface
 EM3LER Emergency version 3 hours, lens - escape route
 EM3LOA Emergency version 3 hours, lens - open areas
 WIE3 3-pole "Wieland - gesis classic" type or compatible connector
 WIE5D 5-pole DALI "Wieland - gesis classic" type or compatible connector
 Schuko-1.5m 3-pole "Schuko" type plug with 3x1.0mm² 1.5m cable
 Schuko-3.0m 3-pole "Schuko" type plug with 3x1.0mm² 3.0m cable
 W625 Designed for the German market to fit 625x625 suspended ceiling
 RAL (MOQ: 10pcs) RAL colour
 *note - price for uncommon RAL colour or quantity less then MOQ could be different from indicated. Ask before placing an order
 DPRZ De-glaring micro-prismatic diffuser
 T830 Colour temperature 3000K, CRI 80+
 T840 Colour temperature 4000K, CRI 80+

OP LT80



DPRZ LT80



Available accessories:



Product: Recessed MTG FRAME S626x626 RAL9003
 Description: Frame for LED luminaire 595x595mm
 installation into plasterboard ceiling (1pcs), white steel