

PAVO P LED

IP44 Surface-mounted LED Luminaire with Opal Diffuser



Type: Wall and ceiling surface-mounted LED luminaire with opal IP44 diffuser and rounded profile.

Specification: Opal PMMA diffuser with IP44 protection rating.
White steel body with quick fix lock.
Luminaire is plastic-wrapped and boxed individually.

Installation: Designed to be fixed onto ceiling or walls of any type, including flammable surfaces.

Application: Indoor. Ideal for common areas in hospitals, colleges and other similar institutions.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Pavo P LED1x1100 D515 T830	Ø280x95	40000	1020	12	80+	3000	0,46
Pavo P LED1x1600 D516 T830	Ø360x105	40000	1620	18	80+	3000	0,69
Pavo P LED1x2000 D517 T830	Ø410x115	40000	2090	22	80+	3000	0,90
Pavo P LED1x3000 D518 T830	Ø410x115	40000	3090	32	80+	3000	0,90
Pavo P LED1x1100 D515 T840	Ø280x95	40000	1080	12	80+	4000	0,46
Pavo P LED1x1600 D516 T840	Ø360x105	40000	1700	18	80+	4000	0,69
Pavo P LED1x2000 D517 T840	Ø410x115	40000	2200	22	80+	4000	0,90
Pavo P LED1x3000 D518 T840	Ø410x115	40000	3200	32	80+	4000	0,90
Pavo P LED1x1100 D515 T830 EM3	Ø280x95	40000	1020	12	80+	3000	0,60
Pavo P LED1x1600 D516 T830 EM3	Ø360x105	40000	1620	18	80+	3000	0,84
Pavo P LED1x1100 D515 T840 EM3	Ø280x95	40000	1080	12	80+	4000	0,60
Pavo P LED1x1600 D516 T840 EM3	Ø360x105	40000	1700	18	80+	4000	0,84

* Tolerance range for optical and electrical data: ±10 %

Options available on request:

- EM3- Emergency version 3 hours (only 12 and 18 W versions)
- MW- MW sensor
- T830- Colour temperature 3000K
- T840- Colour temperature 4000K

Pavo P LED1x1600 D516 T840

