


ANTLIA T LED

Product Group: Spotlights



Images for the product family and options:



Description: A LED track light with deepened opal symmetrical faceted reflector designed for the general lighting
 Diffuser: opal polycarbonate, UV stable, with white coated ring
 Body: aluminum, white finish, with adaptor

General data: Mains voltage: 220-240V, 0/50-60Hz
 Power factor: >0,95
 Light source: LED
 Light source included: Yes
 Light distribution type: Direct
 LED lifetime, h: 50000/L80B50 (75000/L80B50 low power versions)
 Operating temperature range, °C: ta 0...+35
 Protection class IEC: I
 Ingress protection code: IP20
 Mechanical impact resistance: IK02
 EEC: A++

Installation: Surface luminaire is designed to be fixed into 4/6-conductors surface/recessed tracks. Track adaptor (3-phase + N) with phase selector

Environment: Indoor

Application: Retail, showroom, exhibition, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Antlia T LED1x1450 D948 T830 OP	200	200	150	1382	11,7	118	80+	3000	1,00
Antlia T LED1x2000 D949 T830 OP	200	200	150	1936	16,2	120	80+	3000	1,00
Antlia T LED1x2700 D950 T830 OP	200	200	150	2635	23,0	114	80+	3000	1,00
Antlia T LED1x1450 D948 T840 OP	200	200	150	1443	11,7	123	80+	4000	1,00
Antlia T LED1x2000 D949 T840 OP	200	200	150	2023	16,2	125	80+	4000	1,00
Antlia T LED1x2700 D950 T840 OP	200	200	150	2753	23,0	120	80+	4000	1,00

* tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C

Available options:

- DALI Driver with DALI interface
- RAL RAL colour
- T830 Colour temperature 3000K, CRI 80+
- T840 Colour temperature 4000K, CRI 80+

