

CYgni LED

Outdoor accent lighting



Images for the product family and options:



Description: Surface mounted accent LED luminaire
Light distribution type: direct
Optical system: lenses, 30° tempered glass diffuser, impact resistant
Housing: aluminium
Colour: light grey

General data: Mains voltage: 220-240V/50-60Hz
LED lifetime: h: 50000/L80B50
SODM: 3
Protection class (IEC): I
Ingress protection code: IP66
Mechanical impact resistance: IK09
Operating temperature range: °C: -25...+40
Installation: On the horizontal or vertical surface (mounting bracket included). Cable 1.0m, 3x1.5mm²
Environment: Outdoor
Application: Facade illumination

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CR1* (Ra)	CCT*, K	Weight, kg
Cygni LED1x1900 D775 T730 L30	705	82	164	1858	13.9	134	70+	3000	3
Cygni LED1x2400 D776 T730 L30	705	82	164	2508	19.2	131	70+	3000	3
Cygni LED1x3200 D777 T730 L30	705	82	164	3520	27.1	130	70+	3000	3
Cygni LED1x3800 D778 T730 L30	1265	82	164	3681	27.3	135	70+	3000	6
Cygni LED1x4800 D779 T740 L30	1265	82	164	5029	37.5	134	70+	3000	6
Cygni LED1x6400 D780 T730 L30	1265	82	164	7126	53.1	134	70+	3000	6
Cygni LED1x900 D775 T740 L30	705	82	164	1859	13.9	136	70+	4000	3
Cygni LED1x2400 D776 T740 L30	705	82	164	2593	19.2	135	70+	4000	3
Cygni LED1x3200 D777 T740 L30	705	82	164	3630	27.1	134	70+	4000	3
Cygni LED1x3800 D778 T740 L30	1265	82	164	3794	27.3	139	70+	4000	6
Cygni LED1x4800 D779 T740 L30	1265	82	164	5995	37.5	138	70+	4000	6
Cygni LED1x6400 D780 T740 L30	1265	82	164	7259	53.1	137	70+	4000	6

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification.

*Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.


Available options:

T730 Colour temperature 3000K, CRI 70+
T740 Colour temperature 4000K, CRI 70+
DALI Driver with DALI interface and switch-control dimming

L30

Optics with 30x30° beam angle
3LIN 2xCBF3x0.3m Through wiring single phase d=1.5mm² with two flexible cables 3x1.5mm². Cable lengths: 0.3m

STANDARD



Available accessories:



Product: Power supply connector - IP66/IP68, 3x1.5mm²

Description: Quick and easy to connect power supply and luminaire cable connector - IP66/IP68, 3x1.5mm², 450V/10A, 1pc/s