


CYGNI LED

Outdoor accent lighting



Images for the product family and options:



Description:

Surface mounted accent LED luminaire
Light distribution type: direct
Optical system: lenses, 30°, tempered glass diffuser, impact resistant
Housing: aluminium
Colour: light grey

General data:

Mains voltage: 220-240V, 50-60Hz
LED lifetime, h: 50000/L80B50
SDCM: 3
Protection class IEC: I
Ingress protection code: IP66
Mechanical impact resistance: IK09
Operating temperature range, °C: ta -25...+40

Installation:

On the horizontal or vertical surface (mounting bracket included). Cable, 1.0m, 3x1.5mm²

Environment:

Outdoor

Application:

Facade illumination

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI * (Ra)	CCT*, K	Weight, kg
Cygni LED1x1900 D775 T730 L30	705	82	164	1858	13,9	134	70+	3000	3
Cygni LED1x2400 D776 T730 L30	705	82	164	2508	19,2	131	70+	3000	3
Cygni LED1x3200 D777 T730 L30	705	82	164	3520	27,1	130	70+	3000	3
Cygni LED1x3800 D778 T730 L30	1265	82	164	3681	27,3	135	70+	3000	6
Cygni LED1x4800 D779 T730 L30	1265	82	164	5029	37,5	134	70+	3000	6
Cygni LED1x6400 D780 T730 L30	1265	82	164	7126	53,1	134	70+	3000	6
Cygni LED1x1900 D775 T740 L30	705	82	164	1897	13,9	136	70+	4000	3
Cygni LED1x2400 D776 T740 L30	705	82	164	2593	19,2	135	70+	4000	3
Cygni LED1x3200 D777 T740 L30	705	82	164	3630	27,1	134	70+	4000	3
Cygni LED1x3800 D778 T740 L30	1265	82	164	3794	27,3	139	70+	4000	6
Cygni LED1x4800 D779 T740 L30	1265	82	164	5185	37,5	138	70+	4000	6
Cygni LED1x6400 D780 T740 L30	1265	82	164	7259	53,1	137	70+	4000	6

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification


*Photos are for illustration purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Available options:

T730 Colour temperature 3000K, CRI 70+
T740 Colour temperature 4000K, CRI 70+
DALI Driver with DALI interface and switch-control dimming

L30 Optics with 30x30° beam angle
1LIN 2xCBF3x0.3m Through wiring single phase d=1.5 mm² with two flexible cables 3x1.5mm². Cable lengths: 0.3m

STANDARD



Available accessories:



Product: Power supply connector - IP66/IP68, 3x1.5mm²
Description: Quick and easy to connect power supply and luminaire cable connector - IP66/IP68, 3x1.5mm², 450V/10A, 1pcs

Applications:

