


SEASON LED

Emergency Lighting



Description: Surface mounted four-sided LED emergency exit sign
 Light distribution type: direct
 Optical system: opal polycarbonate diffuser
 Housing: steel
 Colour: white (RAL9003)
 Battery charging time: 24 hours (12 hours optional: AUT)
 Battery: NiCd (LiFePO₄ optional: AUT), deep discharge protection
 Recognition distance: 25 meters

General data: Mains voltage: 220-240V, 50-60Hz
 LED lifetime, h: 50000/L80B50
 Operating temperature range, °C: ta 0...+40
 Protection class IEC: I
 Ingress protection code: IP41
 Mechanical impact resistance: IK05

Installation: On the ceiling. Push-in terminal, 4x2x2.5mm²

Environment: Indoor

Application: Emergency exit sign

Product	Length, mm	Width, mm	Height, mm	Illumination mode	Emergency operating time, h	Power in emergency mode, W*	CRI *	CCT, K*	Weight, kg
Season 1PLED C343 OP	240	240	240	M/NM	1	3	80+	6500	1,95
Season 3PLED C344 OP	240	240	240	M/NM	3	3	80+	6500	2,15
Season 1PLED C343 OP AUT	240	240	240	M/NM	1	3	80+	6500	1,95
Season 3PLED C344 OP AUT	240	240	240	M/NM	3	3	80+	6500	2,15
Season CEBLED C345 OP	240	240	240	CEB	-	3	80+	6500	1,65

* Note: pictograms have to be chosen and ordered as a separate item

* -M -maintained (with an option of connecting as non-maintained), NM- non-maintained, system power and output indicates data in emergency mode, tolerance range for optical and electrical data: ±10%, values apply to an ambient temperature of 25°C

Available options:

TEST	Manual test button	CLV	Fitting to low voltage central battery system CEBLV
AUT	Autonomous testing system	EMS	Fitting to emergency monitoring system
CEB	Fitting to central battery system		