


HEZE P LED

Diffuser and Wall Luminaires



Images for the product family and options:



Description: Surface mounted plastic LED luminaire
Light distribution type: direct
Optical system: opal acrylic diffuser, UV resistant
Housing: thermoplastic
Colour: white

General data: Mains voltage: 220-240V, 0/50-60Hz
LED lifetime, h: 50000/L80B50
SDCM: 3
Protection class IEC: II
Ingress protection code: IP65
Mechanical impact resistance: IK08
Operating temperature range, °C: ta -15...+35 (from 0 °C with EM3)

Installation: On the ceiling or wall. Push-in terminal, 2x2x2.5mm² (screw terminal, 2x1.5mm² for E27 version)

Environment: Indoor/outdoor with roof

Application: Office, education, hotel, corridor, staircase, healthcare, bathroom, public place, parking area



Luminaire is available in dark grey body (DGREY). For more information see the option list.

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Heze P 1E27 Z70	295	295	90						1,40
Heze P 2E27 Z71	295	295	90						1,40
Heze P LED1x1200 D960 T830	295	295	90	1107	10,1	110	80+	3000	1,70
Heze P LED1x1650 D961 T830	295	295	90	1547	14,7	105	80+	3000	1,70
Heze P LED1x1200 D960 T840 1G	295	295	90	1167	10,1	115	80+	4000	1,70
Heze P LED1x1650 D961 T840 1G	295	295	90	1631	14,7	111	80+	4000	1,70
Heze P 1E27 Z70 DGREY	295	295	90						1,40
Heze P 2E27 Z71 DGREY	295	295	90						1,40
Heze P LED1x1200 D960 T830 DGREY	295	295	90	1107	10,1	110	80+	3000	1,70
Heze P LED1x1650 D961 T830 DGREY	295	295	90	1547	14,7	105	80+	3000	1,70
Heze P LED1x1200 D960 T840 DGREY	295	295	90	1167	10,1	115	80+	4000	1,70
Heze P LED1x1650 D961 T840 DGREY	295	295	90	1631	14,7	111	80+	4000	1,70

* Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

TECHNICAL DATA SHEET

Available options:

DALI	Driver with DALI interface	MWRFS+off	Integrated microwave (MW) motion sensor with integrated RF (radio wave) receiver. Sensor can serve as slave. Functions: Staircase, Corridor (no dimming control).
DIM	Driver with 1-10V dimming	MWRFS	Integrated microwave (MW) motion sensor with integrated RF (radio wave) receiver. Sensor can serve as slave. Functions: Staircase, Corridor, (no dimming control).
MW	Integrated microwave (MW) motion sensor with on-off control	EM3	Emergency version 3 hours
MWRFM+	Integrated microwave (MW) motion sensor with integrated RF (radio wave) transceiver. Sensor can serve as both master and slave. Functions: Staircase, Corridor, dimming control.	EM3B	Emergency version 3 hours (best available technology)
MWRFM+off	Integrated microwave (MW) motion sensor with integrated RF (radio wave) transceiver. Sensor can serve as both master and slave. Functions: Staircase, Corridor, (no dimming control).	EM3A	Emergency version equipped with an autonomous testing system, 3 hours
MWRFM	Integrated microwave (MW) motion sensor with integrated RF (radio wave) transmitter. Sensor can serve as master. Functions: Staircase, Corridor, dimming control.	EM3D	Emergency version 3 hours with DALI interface
MWRFS+	Integrated microwave (MW) motion sensor with integrated RF (radio wave) receiver. Sensor can serve as slave. Functions: Staircase, Corridor, dimming control.	<i>*note - Operating temperature range for Luminaires with EM option, °C: ta 0... +35</i>	
T840	Colour temperature 4000K, CRI 80+	1G	Strain relief for power supply cable
T830	Colour temperature 3000K, CRI 80+	LOUVER	Decorative louver
		DGREY	Dark grey thermoplastic body

OP

