

INDUSTRY IP66 LED ENDURA

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP66
Nominal power [W]:	54.00; 62.00
Luminous flux [lm]*:	8900; 10500
Colour temperature [K]:	4000
Energy efficiency class:	B
Material of the body:	aluminium
Colour of the body:	grey
Diffuser material:	glass
Diffuser type:	transparent
Mounting version:	surface, suspended
Working temperature [°C]:	from -40 to +60
Dimensions (H/W/T/S) [mm]:	1150/63/55; 1450/63/55
Warranty [years]:	5

CHARACTERISTICS

INDUSTRY IP66 LED is a hermetic beam from the NEXT GEN line, which is a new generation of lamps dedicated to LED technology. The body, made from scratch, made of aluminum profile and subjected to anodization process, provides the luminaire with strength and solidity, and the narrow side profile allows installation in hard to reach places. LEDs from a reputable manufacturer and new LED modules have an impact on very high luminous efficacy: up to 161 lm / W. This guarantees that the required lighting level is achieved and that significant energy savings are achieved. The lampshade is made of UV resistant tempered glass. The combination of materials (aluminum and toughened glass) and a non-dismantled construction with an external connector provides the luminaire with high resistance to harsh environmental conditions. Suitable for surface and suspended mounting.

APPLICATION

The multi-purpose LED luminaire has been designed for use in areas requiring high dust and water resistance. It is especially recommended for use in rooms intended for medical and laboratory purposes as well as in industrial premises.

INDUSTRY IP66 LED ENDURA

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

INDUSTRY IP66 LED ENDURA 54W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
54	4000	8900	1150/63/55	B	>> 552472


INDUSTRY IP66 LED ENDURA 62W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
62	4000	10500	1450/63/55	B	>> 552489

INDUSTRY IP66 LED ENDURA

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



INDUSTRY IP66 LED 110°

Card creation date: 06 grudnia 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer.



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certyfikat CE - Nr:132/2020



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. 532-518-393 (Pn-Pt, 8-16), e-mail: kontakt@lenalighting.pl, www.lenalighting.pl