


DISC A LED

High-bays



Images for the product family and options:



DIM ZHAGA

Description: A high-bay LED luminaire
 Light distribution type: direct
 Optical system: lenses, low glare
 Housing: diecast aluminium
 Colour: black, RAL 9017

General data: Mains voltage: 220-240V, 50/60Hz
 LED lifetime, h: 85000/L80B10
 SDCM: 5
 Protection class IEC: I
 Ingress protection code: IP65
 Mechanical impact resistance: IK08
 Operating temperature range, °C: ta -30... +50

Installation: Suspended. Supplied with suspension hook and out-going cable for easy mounting. Cable, 0.3m, 3x0.75mm²

Environment: Indoor

Application: Industry, warehouse, hall

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI* (Ra)	CCT*, K	Weight, kg
DISC A LED1x18500/14800/11100 J733 T840	250	250	165	9650/ 13750/ 18500	60/ 80/ 100	161/ 172/ 185	80+	4000	1,6
DISC A LED1x28000/22400/16800 J734 T840	261	261	168	17700/ 22800/ 27750	90/ 120/ 150	196/ 190/ 185	80+	4000	1,9
DISC A LED1x37000/29600/22200 J735 T840	301	301	169	23600/ 30900/ 37000	120/ 160/ 200	197/ 193/ 185	80+	4000	2,3
DISC A LED1x18500 J733 T840 DALI	250	250	165	18500	100	185	80+	4000	1,6
DISC A LED1x28000 J734 T840 DALI	261	261	168	27750	150	185	80+	4000	1,9
DISC A LED1x37000 J735 T840 DALI	301	301	169	37000	200	185	80+	4000	2,3
DISC A LED1x18500/14800/11100 J733 T840 DIM ZHAGA18	250	250	165	9650/ 13750/ 18500	60/ 80/ 100	161/ 172/ 185	80+	4000	1,6
DISC A LED1x28000/22400/16800 J734 T840 DIM ZHAGA18	261	261	168	17700/ 22800/ 27750	90/ 120/ 150	196/ 190/ 185	80+	4000	1,9
DISC A LED1x37000/29600/22200 J735 T840 DIM ZHAGA18	301	301	169	23600/ 30900/ 37000	120/ 160/ 200	197/ 193/ 185	80+	4000	2,3

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

*Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.


Available options:

CBF3x1.5-N m Outgoing flexible cable 3x1.5mm², length according to customer specification

CBF5x1.5-N m Outgoing flexible cable 5x1.5mm², length according to customer specification

*note - Please specify the length of outgoing cable before placing an order

STANDARD



Available accessories:



Product: Power supply connector - IP66/IP68, 3x1.5mm²
Description: Quick and easy to connect power supply and luminaire cable connector - IP66/IP68, 3x1.5mm², 450V/10A, 1pcs



Product: Suspension MTG KIT - Saturn LED 1.5m
Description: Suspension kit for Saturn LED high-bay, 1.5 meter

Product: Suspension MTG KIT - Saturn LED 3.0m
Description: Suspension kit for Saturn LED high-bay, 3.0 meters

Product: Suspension MTG KIT - Saturn LED 5.0m
Description: Suspension kit for Saturn LED high-bay, 5.0 meters



Product: Sensor HBPIR ZHAGA 360 D12/12 DIM B (ANT-6-ZT)
Description: Build-in PIR High-bay sensor



Product: Remote Control RC-100
Description: The functionality of the HBPIR are controlled by a number of parameters which can be changed or programmed remotely with an infrared handset RC-100