


**Eyelet\_R** | Movable spotlight | powerLED 1 W DC 350 mA




Efficiency - CRI 80		Cct	lm S - D	Optic
White	<b>82619</b>	M 2700	145 - 74	<b>20</b> Spot (20°)
Black	<b>82620</b>	W 3000	145 - 79	<b>35</b> Flood (34°)
Grey	<b>82621</b>	N 4000	155 - 84	

**Electronics**

89144	89145	99375	99708	99711	+ driver 24V DC 99374 75W 99331 150W
ON/OFF 1 - 2 art. p 138 x 1 22 x h 21	ON/OFF 3 - 6 art. p 138 x 1 22 x h 21	ON/OFF 6 - 12 art. p 138 x 1 22 x h 21	24V DC converter 0/1-10V 1 - 4 art. p 138 x 1 22 x h 21	24V DC converter DALI 1 - 4 art. p 138 x 1 22 x h 21	

**Eyelet\_Q** | Movable spotlight | powerLED 1 W DC 350 mA




Efficiency - CRI 80		Cct	lm S - D	Optic
White	<b>82622</b>	M 2700	136 - 74	<b>20</b> Spot (20°)
Black	<b>82623</b>	W 3000	144 - 79	<b>35</b> Flood (34°)
Grey	<b>82624</b>	N 4000	155 - 84	

**Electronics**

89144	89145	99375	99708	99711	+ driver 24V DC 99374 75W 99331 150W
ON/OFF 1 - 2 art. p 138 x 1 22 x h 21	ON/OFF 3 - 6 art. p 138 x 1 22 x h 21	ON/OFF 6 - 12 art. p 138 x 1 22 x h 21	24V DC converter 0/1-10V 1 - 4 art. p 138 x 1 22 x h 21	24V DC converter DALI 1 - 4 art. p 138 x 1 22 x h 21	

**Eyelet\_R** | Movable spotlight | powerLED 2 W DC 630 mA




Efficiency - CRI 80		Cct	lm S - D	Optic
White	<b>96984</b>	M 2700	219 - 172	<b>15</b> Spot (23°)
Black	<b>96985</b>	W 3000	233 - 154	<b>30</b> Flood (28°)
Grey	<b>96986</b>	N 4000	249 - 165	<b>60</b> W.Flood (65°)

**Electronics**

89147	99376	99105	99710	99713	+ driver 24V DC 99374 75W 99331 150W
ON/OFF 1 - 2 art. p 138 x 1 22 x h 21	ON/OFF 3 - 6 art. p 138 x 1 22 x h 21	ON/OFF 6 - 12 art. p 103 x 1 58 x h 27	24V DC converter 0/1-10V 1 art. p 138 x 1 22 x h 21	24V DC converter DALI 1 art. p 138 x 1 22 x h 21	

**Eyelet\_Q** | Movable spotlight | powerLED 2 W DC 630 mA





Efficiency - CRI 80		Cct	lm S - D	Optic
White	<b>97336</b>	M 2700	219 - 172	<b>15</b> Spot (23°)
Black	<b>97337</b>	W 3000	233 - 154	<b>30</b> Flood (28°)
Grey	<b>97338</b>	N 4000	249 - 165	<b>60</b> W.Flood (65°)

**Electronics**

89147	99376	99105	99710	99713	+ driver 24V DC 99374 75W 99331 150W
ON/OFF 1 - 2 art. p 138 x 1 22 x h 21	ON/OFF 3 - 6 art. p 138 x 1 22 x h 21	ON/OFF 6 - 12 art. p 103 x 1 58 x h 27	24V DC converter 0/1-10V 1 art. p 138 x 1 22 x h 21	24V DC converter DALI 1 art. p 138 x 1 22 x h 21	

**Eyelet65\_R** | Accent lighting | powerLED 2 W DC 630 mA





		Cct	lm S - D	Optic
White	<b>91214</b>	<b>M</b> 2700	219 - 151	<b>15</b> Spot (23°)
Black	<b>91215</b>	<b>W</b> 3000	233 - 171	<b>30</b> Flood (29°)
Grey	<b>91216</b>	<b>N</b> 4000	249 - 183	<b>60</b> Wide Flood (65°)

**Electronics**

89420	99179	99186	83102
ON/OFF 1 - 2 art. p 65 x l 74 x h 27	ON/OFF 3 - 6 art. p 80 x l 100 x h 31	ON/OFF 6 - 12 art. p 92 x l 117 x h 38	DALI 1 - 14 art. p 54 x l 121 x h 26

Accessories Pag. 5

**Eyelet65\_Q** | Accent lighting | powerLED 2 W DC 630 mA



		Cct	lm S - D	Optic
White	<b>91217</b>	<b>M</b> 2700	219 - 151	<b>15</b> Spot (23°)
Black	<b>91219</b>	<b>W</b> 3000	233 - 171	<b>30</b> Flood (29°)
Grey	<b>91220</b>	<b>N</b> 4000	249 - 183	<b>60</b> Wide Flood (65°)

**Electronics**

89420	99179	99186	83102
ON/OFF 1 - 2 art. p 65 x l 74 x h 27	ON/OFF 3 - 6 art. p 80 x l 100 x h 31	ON/OFF 6 - 12 art. p 92 x l 117 x h 38	DALI 1 - 14 art. p 54 x l 121 x h 26

Accessories Pag. 5



Eyelet65 with integrated Snoot accessory


**Accessories**



description	
<b>98624</b>	Steel peg 160 mm
suitable for: Eyelet65_R / Eyelet65_Q	



description	
<b>99746</b>	Snoot
suitable for: Eyelet65_R / Eyelet65_Q	



description	
<b>98669</b>	Steel peg 101 mm
suitable for: Eyelet65_R / Eyelet65_Q	



description	
<b>84992</b>	Wrench for installing the Snoot
suitable for: Eyelet65_R / Eyelet65_Q	