


LIBRA LED

Emergency Lighting



Images for the product family and options:



Description: Surface mounted LED emergency exit sign / escape luminaire
 Light distribution type: direct
 Optical system: opal or clear polycarbonate diffuser, impact resistant
 Housing: polycarbonate, with test button
 Colour: white
 Battery charging time: 24 hours
 Battery: NiCd / LiFePO4
 Recognition distance: 20 meters

General data: Mains voltage: 220-240V, 50-60Hz
 LED lifetime, h: 50000/L70B50
 SDCM: 5
 Protection class IEC: I
 Ingress protection code: IP65
 Mechanical impact resistance: IK08
 Operating temperature range, °C: ta 0...+40

Installation: On the wall. Push-in terminal, 4x2x2.5mm²

Environment: Indoor

Application: Emergency exit sign, escape route lighting (clear version)



Supplied with universal sticker.


Product	Length, mm	Width, mm	Height, mm	Illumination mode	Emergency operating time, h	Power in emergency mode, W*	CRI*	CCT, K*	Weight, kg
Libra 3PLED B234 OP TEST	350	110	60	M/NM	3	1	70+	6500	1,35
Libra 3PLED G117 OP TEST	350	110	60	M/NM	3	1	70+	6500	1,35
Libra 3PLED G117 CLR TEST	350	110	60	M/NM	3	1	70+	6500	1,35
Libra 3PLED G117 OP AUT	350	110	60	M/NM	3	1	70+	6500	1,35
Libra 3PLED G117 CLR AUT	350	110	60	M/NM	3	1	70+	6500	1,35

*M -maintained (with an option of connecting as non-maintained), NM- non-maintained, system power and output indicates data in emergency mode, tolerance range for optical and electrical data: ±10%, values apply to an ambient temperature of 25°C

Available accessories:



Product: Libra PRG SPORT
 Description: White protection grid for LIBRA



Product: Pictogram "Fire hose reel" Libra/Hydra LED
 Description: Pictogram "Fire hose reel" for Libra/Hydra LED