

TEAM
wall recessed / step light




IP66
round: IK 09
other versions: IK 08

ø 160 mm
140 x 140 mm
260 x 140 mm

IP68 connector included

TEAM
bollard



IP66
IK 08

280 x 102 x h. 600 mm
280 x 102 x h. 900 mm

IP68 connector included

on request finishes



.01 black

.02 white



.07 corten

.08 anthracite

standard finishes



.06 grey



.09 bronze

TEAM wall recessed / step light

WHITE LED

3000K CRI>80
220-240V 50/60Hz ⊕
TRIAC dimmable

2700K / 4000K
available on request

→ round



8W | 410 lm (*)
asymmetrical

→ square



8W | 395 lm (*)
asymmetrical

→ rectangular



17,5W | 890 lm (*)
asymmetrical

TEAM bollard

WHITE LED

3000K CRI>80
220-240V 50/60Hz ⊕
TRIAC dimmable

2700K / 4000K
available on request

→ h. 600 mm single emission



8W | 410 lm (*)
asymmetrical

→ h. 600 mm double emission



8W | 395 lm (*)
asymmetrical

→ h. 900 mm single emission



17,5W | 890 lm (*)
asymmetrical

→ h. 900 mm double emission



35W | 1780 lm (*)
asymmetrical