



SMALL LINE PL REFLECTOR



SMALL LINE SL REFLECTOR

CONSTRUCTION		
IP	IP 20	IP 20
IK	IK05 0.70J xx3	IK05 0.70J xx3
Dimensions (mm)	1256/1556 x 132 x 26	956/976 x 252 x 2042
Weight	Max 2 kg	Max 10,7 kg
Colour	○●	○●
INSTALLATION		
Continuous mounted luminaire	✓	-
LED		
Lightsource lumen output	3000 K	6460 lm + 9540 lm
	4000 K	8540 lm + 12610 lm
Luminaire lumen output	3000 K	6660 lm + 9830 lm
	4000 K	8800 lm + 13000 lm
CCT - Correlated Color Temperature	3000 K / 4000 K	3000 K / 4000 K
CRI / SDCM (macadam step)	80/3	80/3
Lifetime	L80B10@50000h	L80B10@50000h
OPTIC		
S/C - symmetric uniform direct-indirect light	S/C 2 x 37°	S/C 2 x 42° + 2 x 42°/42°
UFF (Upward Flux Fraction)	60 %	53 %
DFI (Downward Flux Fraction)	40 %	47 %
ELECTRICAL		
Wattage	57 W - 69 W - 71 W - 87 W	63 W - 88 W
Class	I	I
EEL	A1 - A2	A1 - A2
Dimmable DALI	✓	✓
CO ₂ ≥ 0,9	✓	✓
CONTROL SYSTEMS		
Infrared motion sensor - IR	✓	✓
DIM SMART (bluetooth)	✓	-
STANDARDS		
DIN EN 12464-1	✓	✓