

## SMALL LINE



SMALL LINE PL REFLECTOR



SMALL LINE SL REFLECTOR

CONSTRUCTION			
IP		IP 20	IP 20
IK		IK05 0.70J xx3	IK05 0.70J xx3
Dimensions (mm)		1256/1556 x 132 x 26	956/976 x 252 x 2042
Weight		Max 2 kg	Max 10,7 kg
Colour		○ ●	○ ●
INSTALLATION			
Continuous mounted luminaire		✓	-
LED			
Lightsource lumen output	3000 K	6460 lm ÷ 9540 lm	6940 lm ÷ 9390 lm
	4000 K	8540 lm ÷ 12610 lm	9410 lm ÷ 12710 lm
Luminaire lumen output	3000 K	6660 lm ÷ 9830 lm	7150 lm ÷ 9680 lm
	4000 K	8800 lm ÷ 13000 lm	9700 lm ÷ 13100 lm
CCT - Correlated Color Temperature		3000 K / 4000 K	3000 K / 4000 K
CRI / SDCM (macadam step)		80/3	80/3
Lifetime		L80B10@50000h	L80B10@50000h
OPTIC			
S/C – symmetric uniform direct-indirect light		S/C 2 x 37°	S/C 2 x 42° ÷ 2 x 42°/42°
UFF (Upward Flux Fraction)		60 %	53 %
DFF (Downward Flux Fraction)		40 %	47 %
ELECTRICAL			
Wattage		57 W - 69 W - 71 W - 87 W	63 W - 88 W
Class		I	I
EEL		A1 - A2	A1 - A2
Dimmable DALI		✓	✓
COSφ ≥ 0,9		✓	✓
CONTROL SYSTEMS			
Infrared motion sensor - IR		✓	✓
DIM SMART (bluetooth)		✓	-
STANDARDS			
DIN EN 12464-1		✓	✓