

ANGLE LED

Outdoor accent lighting



Description:

Wall mounted LED luminaire
Light distribution type: direct
Optical system: tempered glass diffuser
Housing: aluminum

General data:

Colour: dark grey (RAL 7040)
Main voltage: 200-240V, 50-60Hz
LED lifetime: ≥ 50000 / L80B50
SDCM: 5
Protection class: IEC I
Ingress protection code: IP65
Mechanical impact resistance: IK08
Operating temperature range: -10°C to $+30^{\circ}\text{C}$ / $+45^{\circ}\text{C}$

Installation:

On the wall. Screw terminal. $3 \times 9 \times 2.5 \text{ mm}^2$

Environment:

Outdoor

Application:

Facade illumination, parking area, park, public space

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CR+ (Ra)	CCT*, K	Weight, kg
Angle LED Is 900 / 788 T830	111	53	111	845	8.3	102	80+	3000	0.61
Angle LED Is 900 / 788 T840	111	55	111	875	8.5	103	80+	4000	0.61


*Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25°C . NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification.

*Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Available options:

T830 Colour temperature 3000K, CRI 80+
T840 Colour temperature 4000K, CRI 80+

STANDARD



Applications:

