


ANGLE LED

Outdoor accent lighting



Description:	Wall mounted LED luminaire Light distribution type: direct Optical system: tempered glass diffuser Housing: aluminium Colour: dark grey, RAL7043
General data:	Mains voltage: 220-240V, 50-60Hz LED lifetime, h: 50000/L80B50 SDCM: 5 Protection class IEC: I Ingress protection code: IP65 Mechanical impact resistance: IK08 Operating temperature range, °C: ta -30...+45
Installation:	On the wall. Screw terminal, 3x1x2.5mm²
Environment:	Outdoor
Application:	Facade illumination, parking area, park, public space

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI * (Ra)	CCT*, K	Weight, kg
Angle LED1x900 J788 T830	111	95	111	840	8,5	99	80+	3000	0,61
Angle LED1x900 J788 T840	111	95	111	875	8,5	103	80+	4000	0,61


*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

*Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Available options:

T830 Colour temperature 3000K, CRI 80+

T840 Colour temperature 4000K, CRI 80+



Applications:

