

FORMA G LED

Acoustic luminaires



Images for the product family and options:



Description: A decorative ring-shaped LED luminaire with preserved moss panel in three sizes to fit wide range of applications

Light distribution: direct
Optical system: opal PMMA diffuser, UV stabilized
Housing: steel
Colour: white DALI 90035
Main voltage: 220-240V, 50/60Hz
LED lifetime: > 50000h/80000
SDCM: 3
Protection class: IEC: I
Ingress protection code: IP40
Mechanical impact resistance: IK02
Operating temperature range: °C: ta 0...+35

General data: Mains voltage: 220-240V, 50/60Hz

LED lifetime: > 50000h/80000
SDCM: 3
Protection class: IEC: I
Ingress protection code: IP40
Mechanical impact resistance: IK02
Operating temperature range: °C: ta 0...+35

Installation: Surface luminaire is designed to be fixed to ceiling of any type or suspended. Multiple wire suspension, cable cap and decorative cable accessories are available on request. Push-in terminal, 3x2x2.5mm²

Environment: Indoor

Application: Office, education, retail, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CR ⁺ (Ra)	CCT*, K	Weight, kg
Forma G LED1x2050 J55 T830 OP	600	600	80	1924	55.9	34.6	80+	3000	6.4
Forma G LED1x2750 J55 T830 OP	600	600	80	2621	23.6	111	80+	3000	6.4
Forma G LED1x3800 J55 T830 OP	600	600	80	3603	34.6	104	80+	3000	6.4
Forma G LED1x3300 J55 T830 OP	900	900	80	3148	26.4	119	80+	3000	12.0
Forma G LED1x4500 J55 T830 OP	900	900	80	4289	37.7	114	80+	3000	12.0
Forma G LED1x6200 J60 T830 OP	900	900	80	5836	54.9	107	80+	3000	12.0
Forma G LED1x4400 J61 T830 OP	1200	1200	80	4197	34.8	121	80+	3000	18.8
Forma G LED1x6000 J62 T830 OP	1200	1200	80	5719	49.9	115	80+	3000	18.8
Forma G LED1x6250 J706 T830 OP	1200	1200	80	7861	72.4	109	80+	3000	18.8
Forma G LED1x2050 J55 T840 OP	600	600	80	2014	16.9	119	80+	4000	6.4
Forma G LED1x2750 J55 T840 OP	600	600	80	2744	23.6	116	80+	4000	6.4
Forma G LED1x3800 J55 T840 OP	600	600	80	3772	34.6	109	80+	4000	6.4
Forma G LED1x3300 J58 T840 OP	900	900	80	3295	26.4	125	80+	4000	12.0
Forma G LED1x4500 J59 T840 OP	900	900	80	4431	37.7	119	80+	4000	12.0
Forma G LED1x6200 J60 T840 OP	900	900	80	6173	54.9	112	80+	4000	12.0
Forma G LED1x4400 J61 T840 OP	1200	1200	80	4394	34.8	126	80+	4000	18.8
Forma G LED1x6000 J62 T840 OP	1200	1200	80	5987	49.9	120	80+	4000	18.8
Forma G LED1x6250 J706 T840 OP	1200	1200	80	8231	72.4	114	80+	4000	18.8

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

*Photos are for illustrative purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors

Available options:

T830	Colour temperature 3000K, CRI 80+	COR1min	Driver with Corridor function 1min (switch off after 1 min.)
T840	Colour temperature 4000K, CRI 80+	COR30min	Driver with Corridor function 30min (switch off after 30 min.)
DSGZ LT 80	De-glaring macro-prismatic diffuser, matt		
DALI	Driver with DALI interface and switch-control/dimming	CBF3-2.0m clear	Cable 3x0.75mm ² for suspended luminaire up to 2.0 meters, transparent
BLT	Integrated wireless control unit and driver for lighting control via mobile device (via Bluetooth)	CBF3-3.0m clear	Cable 3x0.75mm ² for suspended luminaire up to 3.0 meters, transparent
KIRBLT	Integrated wireless control unit and driver for lighting control via mobile device (KIR system app), on/off	CBF5-2.0m clear	Cable 5x0.75mm ² for suspended luminaire up to 2.0 meters, transparent
KIRBLT DALI	Integrated wireless control unit and driver for lighting control via mobile device (KIR system app), DALI with integrated DALI	CBF5-3.0m clear	Cable 5x0.75mm ² for suspended luminaire up to 3.0 meters, transparent
COR	Driver with Corridor function (never off)	RAL	RAL colour