


FORMA G LED

Acoustic luminaires



Images for the product family and options:



Description:

A decorative ring-shaped LED luminaire with preserved moss panel in three sizes to fit wide range of applications
Light distribution: direct
Optical system: opal PMMA diffuser, UV stabilized
Housing: steel
Colour: white, RAL 9003S

General data:

Mains voltage: 220-240V, 0/50-60Hz
LED lifetime, h: 50000/L80B10
SDCM: 3
Protection class IEC: I
Ingress protection code: IP40
Mechanical impact resistance: IK02
Operating temperature range, °C: ta 0...+35

Installation:

Surface luminaire is designed to be fixed to ceiling of any type or suspended. Multiple wire suspension, cable cap and decorative cable accessories are available on request. Push-in terminal, 3x2x2.5mm2

Environment:

Indoor

Application:

Office, education, retail, public place


Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI * (Ra)	CCT*, K	Weight, kg
Forma G LED1x2050 J155 T830 OP	600	600	80	1924	16,9	114	80+	3000	6,4
Forma G LED1x2750 J156 T830 OP	600	600	80	2621	23,6	111	80+	3000	6,4
Forma G LED1x3800 J157 T830 OP	600	600	80	3603	34,6	104	80+	3000	6,4
Forma G LED1x3300 J158 T830 OP	900	900	80	3148	26,4	119	80+	3000	12,0
Forma G LED1x4500 J159 T830 OP	900	900	80	4289	37,7	114	80+	3000	12,0
Forma G LED1x6200 J160 T830 OP	900	900	80	5896	54,9	107	80+	3000	12,0
Forma G LED1x4400 J161 T830 OP	1200	1200	80	4197	34,8	121	80+	3000	18,8
Forma G LED1x6000 J162 T830 OP	1200	1200	80	5719	49,8	115	80+	3000	18,8
Forma G LED1x8250 J706 T830 OP	1200	1200	80	7861	72,4	109	80+	3000	18,8
Forma G LED1x2050 J155 T840 OP	600	600	80	2014	16,9	119	80+	4000	6,4
Forma G LED1x2750 J156 T840 OP	600	600	80	2744	23,6	116	80+	4000	6,4
Forma G LED1x3800 J157 T840 OP	600	600	80	3772	34,6	109	80+	4000	6,4
Forma G LED1x3300 J158 T840 OP	900	900	80	3295	26,4	125	80+	4000	12,0
Forma G LED1x4500 J159 T840 OP	900	900	80	4491	37,7	119	80+	4000	12,0
Forma G LED1x6200 J160 T840 OP	900	900	80	6173	54,9	112	80+	4000	12,0
Forma G LED1x4400 J161 T840 OP	1200	1200	80	4394	34,8	126	80+	4000	18,8
Forma G LED1x6000 J162 T840 OP	1200	1200	80	5987	49,8	120	80+	4000	18,8
Forma G LED1x8250 J706 T840 OP	1200	1200	80	8231	72,4	114	80+	4000	18,8

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

*Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Available options:

T830	Colour temperature 3000K, CRI 80+	COR1min	Driver with Corridor function 1min (switch off after 1 min.)
T840	Colour temperature 4000K, CRI 80+	COR30min	Driver with Corridor function 30min (switch off after 30 min.)
DPRZ LT80	De-glaring micro-prismatic diffuser, matt		
DALI	Driver with DALI interface and switch-control dimming	CBF3-2.0m clear	Cable 3x0.75mm ² for suspended luminaire up to 2.0 meters, transparent
BLT	Integrated wireless control unit and driver for lighting control via mobile device (via Bluetooth)	CBF3-3.0m clear	Cable 3x0.75mm ² for suspended luminaire up to 3.0 meters, transparent
KRBLT	Integrated wireless control unit and driver for lighting control via mobile device (KR system app), on/off	CBF5-2.0m clear	Cable 5x0.75mm ² for suspended luminaire up to 2.0 meters, transparent
KRBLT DALI	Integrated wireless control unit and driver for lighting control via mobile device (KR system app), DALI with integrated PS	CBF5-3.0m clear	Cable 5x0.75mm ² for suspended luminaire up to 3.0 meters, transparent
COR	Driver with Corridor function (never off)	RAL	RAL colour



Available accessories:



Product: Suspension MTG KIT SUSI
Description: Suspension wire set "I" type, 1.5m adjustable, 1pcs
**note - at least 3pcs MTG KIT SUSI for one fitting required. For exact quantity please refer to installation manual*



Product: CAP cable 3x0.75 2.0m, clear
Description: Cable 3x0.75mm² for suspended luminaire up to 2.0 meters, transparent



Product: 3-point Suspension MTG KIT with round cap, white/ light grey/ black
Description: Suspension wire set with cap 3x"I" type, 1.5m adjustable, 1pcs
**note - for compatibility with exact product please refer to installation manual*



Product: CAP4, light grey/ white/ black
Description: Square decorative metal cap for hiding cable inlet with suspension wire attachment point, push-in terminals 3x1x1.5mm², light grey/ white/ black



Product: CAP5, light grey/ white/ black
Description: Square decorative metal cap for hiding cable inlet with suspension wire attachment point, push-in terminals 5x1x1.5mm², light grey/ white/ black

Product: CAP cable clip D6.3mm SET clear
Description: Cable and suspension wire clip set, 4pcs. For cable diameter up to 6,3mm and wire diameter 1mm