


HAUD LED

Acoustic Luminaires



Images for the product family and options:



Description:

Acoustic suspended decorative LED luminaire
Light distribution type: direct/indirect
Optical system: opal polycarbonate diffuser
Housing: aluminium
Colour: made to the customer's specification
Mains voltage: 220-240V, 0/50-60Hz
LED lifetime, h: 50000/L80B10
SDCM: 3
Protection class IEC: I
Ingress protection code: IP40
Mechanical impact resistance: IK05
Operating temperature range, °C: ta 0...+35

General data:

Suspended (wire and cap to be ordered separately). Cable 2.0m, 3x0.75mm², transparent

Installation:

Indoor

Environment:

Application:

Office, education, hotel, retail, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI* (Ra)	CCT*, K	Weight, kg
Haud LED1x1650/1050 J413 T840 OP LT80 M... (felt color code)	1159	50	99	2644	21,0	125	80+	4000	3,9
Haud LED1x2200/1450 J414 T840 OP LT80 M... (felt color code)	1159	50	99	3604	29,4	122	80+	4000	3,9
Haud LED1x3050/1950 J415 T840 OP LT80 M... (felt color code)	1159	50	99	4953	43,1	114	80+	4000	3,9
Haud LED1x2050/1400 J416 T840 OP LT80 M... (felt color code)	1439	50	99	3392	26,4	128	80+	4000	4,8
Haud LED1x2750/1900 J417 T840 OP LT80 M... (felt color code)	1439	50	99	4622	37,8	122	80+	4000	4,8
Haud LED1x3800/2600 J418 T840 OP LT80 M... (felt color code)	1439	50	99	6354	54,9	116	80+	4000	4,8

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

*Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Available options:

T830 Colour temperature 3000K, CRI 80+
T840 Colour temperature 4000K, CRI 80+
OP LT80 Opal diffuser with high light transmittance
DPRZ LT80 De-glaring micro-prismatic diffuser with matt light scattering layer
DALI Driver with DALI interface and switch-control dimming
DALisep Driver with DALI interface and with possibility to control down and up light separately
PULL Pull switch device, on/off

PULLDIM Pull switch device and driver with switch-control dimming


*note - For PULL and PULLDIM options luminaire housing is 50mm longer and switch is positioned at the end of luminaire

Lsep Option that enables to control (on/off) down and up lights separately


RAL RAL colour

M... (felt color code) With Fabric cover, height 100mm

OP LT80



DPRZ LT80



Available accessories:



Product: Suspension MTG KIT SUSI
Description: Suspension wire set "I" type, 1.5m adjustable, 1pcs
**note - 2pcs MTG SUSI KIT for 1 luminaire required*



Product: CAP cable clip D6.3mm SET clear
Description: Cable and suspension wire clip set, 4pcs.
For cable diameter up to 6,3mm and wire diameter 1mm



Product: CAP4, light grey/ white/ black
Description: Square decorative metal cap for hiding cable inlet with suspension wire attachment point, push-in terminals 3x1x1.5mm², light grey/ white/ black



Product: CAP5, light grey/ white/ black
Description: Square decorative metal cap for hiding cable inlet with suspension wire attachment point, push-in terminals 5x1x1.5mm², light grey/ white/ black

Material colour:



Natural colour:

